

Ordering Information:

A2008WV-XP - ** - ***
1 2 3

1.Part No.

2.Material:

(Blank): Nylon 66,UL94V-0(Natural)

46: Nylon 46,UL94V-0(Natural)

GWT: Nylon 66,UL94V-0(Beige),


IEC 60335-1,5th Edition

Glow Wire Capable.

3.Finish:

(Blank): Tin over Nickel

G: Gold over Nickel



SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 30mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1000V AC/minute

Pin Material: Brass

Ordering Information & Dimensions

Part No.	Dimensions(mm)	
	A	B
A2008WV- 2P	2.00	6.00
A2008WV- 3P	4.00	8.00
A2008WV- 4P	6.00	10.00
A2008WV- 5P	8.00	12.00
A2008WV- 6P	10.00	14.00
A2008WV- 7P	12.00	16.00
A2008WV- 8P	14.00	18.00
A2008WV- 9P	16.00	20.00
A2008WV- 10P	18.00	22.00
A2008WV- 11P	20.00	24.00
A2008WV- 12P	22.00	26.00
A2008WV- 13P	24.00	28.00
A2008WV- 14P	26.00	30.00
A2008WV- 15P	28.00	32.00
A2008WV- 16P	30.00	34.00

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1
DRN	CHK	APVD
Dengchun Yi	DianKui Wan	Jack Yin

2.00mm PITCH 180° DIP WAFER

General Tolerance
x.xx±0.25
x.xxx±0.20
x.xxxx±0.15
ANGLES ±1°

THIRD ANGLE
PROJECTION

DRAWING NO

A2008WV-XP

REV
A0

REV	DESCRIPTION	DATE
A0	NEW RELEASE	2005.05.10