



LED colour(LED颜色)	Part No.	料号
Whiler(白色)	K6-6154D-01	
Red(红色)	K6-6154D-02	
Blue(蓝色)	K6-6154D-03	
Green(普绿)	K6-6154D-04	
Yellow(黄色)	K6-6154D-05	②
Orange(橙色)	K6-6154D-06	
Jade green(翠绿)	K6-6154D-07	

## Typical Specifications

- Rating : DC 30V 30mA
- Insulation Resistance : 100MΩ Min
- Dielectric Strength : AC 250V for 1 minute
- Operating Force : 260±50 gf
- Contact Resistance : 50mΩ MAX
- Life : 100,000 Cycles Min

⑥	Cap	—	1	PC	—	—
⑤	LED	—	1	—	—	—
④	Button	—	1	PA66	White	—
③	Contact	—	1	SUS	Ag Plating	—
②	Terminal	—	4	Brass	Ag Plating	—
①	Housing	—	1	PA66	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	TITLE: LED Tact Switch		
DRAWN	LIUCAN	2022.9.12	PART NO. K6-6154D-□□		
APPROVALS					

TOLERANCES ARE	30~以上	±0.30	ANGLE ±2°	UNIT: mm SCALE: 1:1	PROJ: ②
	10~30	±0.20			
	5~10	±0.15			
	~ 5	±0.10			

ECN NO.	REV.	DATE.	NEW	—	—	—
DESCRIPTION.				CHANGE.	CHECK.	APPRO.
—	A	—	—	—	—	—

HRO

ELECTRONICS CO.,LTD

®