



NOTE
 MATERIAL & FINISH
 INSULATOR: PBT 30%GF (UL94 V-0)
 CONTACT: PHOSPHOR BRONZE, GOLD OVER NI

ELECTRICAL & MECHANICAL
 CURRENT RATING: 1.0A
 CONTACT RESISTANCE: 20mΩ MAX.
 INSULATION RESISTANCE: 1000MΩ MIN.
 WITHSTAND VOLTAGE: 500V AC/MINUTE
 OPERATION TEMPERATURE: -40°C TO +105°C

SECTION B-B

SECTION A-A

PART NO.

Z-S5224 *** * B 0 0 0 0

No. of Pins
 06P 08P 10P
 12P 14P 16P
 18P 20P 22P
 24P 16P 30P
 34P 36P 40P
 44P 50P 60P
 64P

Color Insulator
 B=Black
 G=Grey

PLATING
 1=GOLD FLASH
 2=GOLD 3U"
 3=GOLD 5U"
 4=GOLD 10U"
 5=GOLD 15U"
 6=GOLD 30U"
 7=GOLD FLASH/NI
 8=GOLD 3U"/NI
 9=GOLD 5U"/NI
 A=GOLD 10U"/NI
 B=GOLD 15U"/NI
 C=GOLD 30U"/NI

UNITS		NAME:	
■mm □INCH		2.00mm IDC SOCKET WITH BUMP (F TYPE)	
GENERAL TOLERANCES: (UNLESS SPECIFIED)		PART NO:	
		Z-S5224***B0000	
	mm	INCH	APPD:
4 PLACE	± **	±	CHKD:
3 PLACE	± **	±	
2 PLACE	± 0.25	±	DRAWN:
1 PLACE	± 0.40	±	
ANGULAR:	X°±**	X°±	

NAME:
2.00mm IDC SOCKET WITH BUMP (F TYPE)

PART NO:
Z-S5224***B0000

APPD:

CHKD:

DRAWN:

nexttron
 NEXTRONICS ENGINEERING CORP.

TITLE:
CUSTOMER DWG

DWG NO:

SCALE: SHEET: REV.:

4 / 1 1 / 1 A

A	NEW RELEASED	3/16'12	
REV.	DESCRIPTION	DATE	APPD