



- Typical Specifications
1. Rating : DC 12V 50mA
 2. Operating Force : 250 ± 50 gf
 3. Contact Resistance : 100mΩMAX
 4. Life : 200,000 Cycles Min
 5. LED Life: 100,000 Hour Min

LED colour (LED颜色)	Part No. (料号)
White (白色)	K6-1212A01
Red (红色)	K6-1212A02
Blue (蓝色)	K6-1212A03
Green (绿色)	K6-1212A04
Yellow (黄色)	K6-1212A05
Orange (橙色)	K6-1212A06

PCB Layout (pattern Side)

② Terminal	Phosphor bronze	Ag Plating
① Housing	Nylon	Black
ITEM	PART NAME	TER. NO. QTY.
APPROVALS	DATE	FINISHING
DRAWN	QIFEEG.XU	2013/11/11
CHECKED		
APPROVALS		
TOLERANCES ARE	30~45L ±0.30	ANGLE ±2°
	10~30 ±0.20	UNIT: mm
	5~10 ±0.15	SCALE: 1:1
	~5 ±0.10	DRAWING NO.

RAYON
ELECTRONICS CO., LTD

TITLE: LED Tact Switch

PART NO. K6-1212A

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			