








RoHS

CAD GENERATED DRAWING. DON'T CHANGE BY HAND.

REV.	ECN. NO.	APPD.



CIRCUIT DIAGRAM



PCB. WELDING DRAWING

Specification

Operating Life	100,000
Contact rating	50mA@12V DC.
Insulation resistance	1011Ω min.
Contact resistance	100mΩ max. initial
Dielectric Strength	250 V AC(1mm)
Travel	0.3±0.1mm
Storage Temperature	-30° C to 85° C

Mechanical

ITEM	DESCRIPTION	MATERIAL	QTY	FINISH/COLOR
E	Button	PPA	1	Black
D	COVER	Brass	1	Cleaning
C	DOME	Stainless Steel	1	Plated Ag
B	HOUSING	PPA	1	Black
A	PIN	PHOSPHOR BRONZE	1	Plated Ag

Type	Operation Force (gf)	Height (mm)	Button	Leads Shape (G, J, T)	Ground pin (0, 1)	Pins (Option 0, 1)
BTSOF002	250±50	Q 15.0	B (BLACK)	G	0 (None)	0 (None)
		P 13.0				
		O 12.0				
		N 11.0				
		M 10.0				
		L 9.0				
		K 8.5				
		J 8.0				
		H 7.5				
		G 7.0				
1	160±50	F 6.5				
		E 6.0				
		D 5.5				
		C 5.0				
		B 4.5				
		A 4.3				

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Bozhong TECHNOLOGY CO.,LTD AND SHALL NOT BE REPRODUCED.

X. ±0.50	X. ° ±2°
.X ±0.30	.X° ±1°
.XX ±0.10	.XX° ±0.5°
.XXX ±0.05	

UNITS	MAT'L	FINISH	Q'TY
mm	/	/	/



东莞市博众电气有限公司
Dongguan Bozhong Electrical Co., Ltd

PART NO.
BTSOF002


TITLE:
TACTILE SWITCH 12x12mm

APPD: ROGER

DWG NO.:
BTSOF002

CHKD: ROC

DR: BILLY WANG 2020/08/21



SCALE	SHEET	REV.
1/1	1/1	A1

Packaging:
A reel of 500 pieces