



额定负荷 Rating	DC 12V/50mA
接触电阻 Contact Resistance	100mΩ max.
绝缘电阻 Insulation resistance	DC:100V 60S 100MΩ min.
抗电强度 Dielectric strength	AC:250V/(50~60HZ) 60S min.
操作力 Operation force	160/250±50gf
寿命试验 Operating Life	100,000 cycles
行程 Travels	0.30±0.1mm

OPERATING FORCE		
VI GOR	180 ± 50gf	
	250 ± 50gf	
	350 ± 50gf	

TOTAL HEIGHT		
G	Ø	Ø
4.3	3.5	7.5
4.5	3.5	8.0
5.0	3.5	8.5
5.5	3.5	9.0
6.0	3.5	9.5
6.5	3.3	10
7.0	3.3	10.5

PCB. 焊接图
PCB. WELDING DRAWING

电路图
CIRCUIT DIAGRAM



一般公差
GENERAL TOLERANCE

>=0-2<	±0.15
>=2-5<	±0.25
>=5	±0.35
角度 ANGLE	±0.5°
未注尺寸公差 (mm)	

项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QTY	表面处理/颜色 FINISH/COLOR
G	按钮	PPA	1	黑色
F	盖板	PPA	1	黑色
E	防尘胶	硅胶	1	黑色
D	防水层	聚酰亚胺	1	橙黄色
C	弹片	不锈钢	1	镀银
B	本体	PPA	1	黑色
A	卡件	黄铜	1	镀银

设计 Jack Jin	图面 单位 A4	东莞市美韩电子科技有限公司 Dongguan Usakro Electronic Technology Co., Ltd.	1 : 1	DWG NO.	型号 :UK-B02123-G7.0-250	SIZE A4				
审核 Jacky Zhong	比例 重量 页码 版次						1 of 1	PART NO.	规格 : 6*6 防水/插件	VIER
批准 Tony Meng	1/1 A/0									