



Recommended PCB Layout

PART NO	H
U-A-24DD-W-11	6.30
U-A-24DD-W-12	6.80

规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

③	②	①	ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Base	—	1	NYLON					
②	Terminal	—	4	Phosphor Bronze			Ag Plated		
①	Housing	—	1	SPCC			Sn Plated		
APPROVALS				DATE					
DRAWN				xu qi feng	2018/8/1		HROELECTRONICS CO.,LTD		
CHECKED				TITLE:		USB CONNECTOR			
APPROVALS				PART NO.					
TOLERANCES ARE				30~ØL ±0.30	ANGLE	UNIT: mm	SCALE: 1:1	PROJ:	
				10~30 ±0.25				SHEET 1 OF 1	
				5~10 ±0.20	±2'	DRAWING NO.			
				~5 ±0.15					
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.			
	A		NEW						