



Specificationsxxb

规格:

Voltage rating:350V AC/DC

额定电压: 350V AC/DC

Current rating:4A AC/DC

额定电流: 4A AC/DC

Withstanding voltage:1700V AC/minute

耐受电压: 1700V AC/分钟

Temperature range:-25°C~+85°C

温度范围: -25°C~+85°C

Insulation resistance:≥1000MΩ

绝缘电阻: ≥1000MΩ

Contact resistance:≤30mΩ

接触电阻: ≤30mΩ XKB

After environmental testing:≤20mΩ

环境测试后: ≤20兆欧

X1800 T -PSN



⊙ Series Number

⊙ Category: T-terminal

⊙ Material: P-Phos phor bronze

⊙ Plating Style: SN-Bright tin plating

X1800T-PSN	Phosphor Bronze	AWG#28-30	1.8mm(Max)	Stamping Before plating 30u"MIN Ni;70u"Sn	X1800H
XPART NO	Material	Wire Range	Insulation O.D	Finish	Suitable XKB Terminal

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.helxkb.com

XKB	ANGLAR	±5°
	L ≤ 4	±0.2
	4 < L ≤ 16	±0.3
	16 < L ≤ 63	±0.4
	L > 63	±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE: X1800T-PSN
DWN	DATE	VIEW:	PART NO.: 2.54 mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT 1.0g SHEET 1/1 REVISION A0