


技术指标:

1. 塑件表面应光洁、无毛边、无明显收线、缺陷、裂纹等现象。
2. 温度范围:  $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ 。
3. 额定电压: 50V, AC, DC。
4. 接触电阻:  $\leq 0.02\Omega$ 。
5. 绝缘电阻:  $\geq 100M\Omega$ 。



Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	1.50	4.50	08	10.50	13.50
03	3.00	6.00	09	12.00	15.00
04	4.50	7.50	10	13.50	16.50
05	6.00	9.00	11	15.00	18.00
06	7.50	10.50	12	16.50	19.50
07	9.00	12.00	13	18.00	21.00

APPROVALS		DATE	DRAWING NO.		TITLE:	
DRAWN	G.M.Chen	2015/7/17	DEALON 德之隆® ELECTRONICS CO.,LTD		ZH-XXA 1.5 Pitch 直插	
CHECKED			PART NO.		SCALE: 1:1	
APPROVALS			UNIT: mm		SHEET 1 OF 1	
TOLERANCES ARE		30 <sup>±0.15</sup>	±0.30	ANGLE	PROJ.	
		10 <sup>±0.10</sup>	±0.20	±2°		
		5 <sup>±0.05</sup>	±0.15			
ECN NO.	REV.	DATE.	DESCRIPTION.		PROJ.	
	A		NEW			
CHANGE.		CHECK.	APPRO.			