



* CRITICAL DIMENSION

- ELECTRICAL CHARACTERISTICS
1. RATING: DC 30V 0.1A
 2. CONTACT RESISTANCE: 100mΩ MAX
 3. INSULATION RESISTANCE: 100MΩ MIN
 4. DIELECTRIC STRENGTH: AC 250V (50~60Hz)/60S
- MECHANICAL CHARACTERISTICS
1. PRACTICAL TEMPERATURE RANG: -40℃~+85℃
 2. OPERATING FORCE: 250±50gf
 3. MECHANICAL LIFE: 20,000 cycles

NO.	PART NAME	Q'TY	MATERIAL	FINSH/COLOR
7	CAM STICK	1	SUS	NATURAL
6	TERMINAL	6	BRASS STRIP	Ag COATING
5	CASE	1	PA66	GRAY
4	CONTACT	2	BRONZE	Ag CLAD
3	COVER	1	PPA	BLACK
2	SPRING	1	SUS	NATURAL
1	KNOB	1	POM	BLUE

X.	± 0.50	X.°	± 2°	UNITS
.X	± 0.30	.X°	± 1°	mm
.XX	± 0.10	.XX°	± 0.5°	MAT'L
.XXX	± 0.05			FINISH

OPERATION FORCE: 250GF

深圳市怡远科技有限公司
 SHENZHEN YIYUAN TECHNOLOGY CO., LTD

PART NO. YTS70L250CU
 APPD: ROGER
 CHKD: ROC
 DR: BILLY WANG 2020/08/21

TITLE: 按钮7.0*7.0 编辑 2*3材料
 DWG NO.: YTS70L250CU

SCALE: 1/1
 SHEET: 1/1
 REV: A1