


**Surface Mount Schottky Barrier Rectifier**  
**Reverse Voltage - 20 to 200 V**  
**Forward Current - 1.0 A**



### FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

### MECHANICAL DATA

- Case: SOD-123FL
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 15mg 0.00048oz

### Absolute Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	K12	K14	K16	K18	K110	K112	K115	K120	Units				
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	20	40	60	80	100	120	150	200	V				
Maximum RMS voltage	$V_{RMS}$	14	28	42	56	70	84	105	140	V				
Maximum DC Blocking Voltage	$V_{DC}$	20	40	60	80	100	120	150	200	V				
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1.0							A					
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	30							A					
Max Instantaneous Forward Voltage at 1 A	$V_F$	0.55		0.70		0.85		0.90		V				
Maximum DC Reverse Current $T_a = 25^\circ\text{C}$ at Rated DC Reverse Voltage $T_a = 100^\circ\text{C}$	$I_R$	0.3 10		0.2 5		0.1 2		mA						
Typical Junction Capacitance <sup>(1)</sup>	$C_j$	110		80				pF						
Typical Thermal Resistance <sup>(2)</sup>	$R_{\theta JA}$	100							°C/W					
Operating Junction Temperature Range	$T_j$	-55 ~ +150							°C					
Storage Temperature Range	$T_{stg}$	-55 ~ +150							°C					

( 1 ) Measured at 1 MHz and applied reverse voltage of 4 V D.C

( 2 ) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current






Fig.6- Typical Transient Thermal Impedance





Plastic surface mounted package; 2 leads

SOD-123FL



The recommended mounting pad size

