


RECOMMENDED PCB PATTERN DIM.

TOLERANCE : ±0.05

NOTES:

- HUOSING: PA9T HIGH-TEMP THERMOPLASTIC UL94V-0 COLOR:BLACK
- TERMINAL:PHOSPHOR BRONZE  
PLATING:1μ" GOLD FLASH OVERALL 50~100μ" NICKEL UNDER PLATED.
- CODING INFORMATION: LB330-GxxS-B1R



3D VIEW

- PACKING: R: CARRIER REEL WITH CAP TYPE
- COLOR:BLACK
- SOCKET
- PIN
- PLATING: G:GOLD FLASH
- 0.8 BTB
- HEIGHT: 30--3.0H;35--3.5H; 40--4.0H;45--4.5H;
- LXWCONN BTB CONNECTOR SERIES

MATING HEIGHT	PLUG (H.)	SOCKET (H.)	NO.of contacts	Dimensions					NO.of contacts	Dimensions				
				A.	B.	C.	D.	E.		A.	B.	C.	D.	E.
4.0	1.0	3.0	4	3.50	0.80	1.86	2.60	4.00	54	23.50	20.80	21.86	22.60	
4.5	1.0	3.5	6	4.30	1.60	2.66	3.40		56	24.30	21.60	22.66	23.40	
5.0	1.0	4.0	8	5.10	2.40	3.46	4.20		58	25.10	22.40	23.46	24.20	
5.5	1.0	4.5	10	5.90	3.20	4.26	5.00		60	25.90	23.20	24.26	25.00	
6.0	2.0	4.0	12	6.70	4.00	5.06	5.80		62	26.70	24.00	25.06	25.80	
6.5	2.0	4.5	14	7.50	4.80	5.86	6.60		64	27.50	24.80	25.86	26.60	
			16	8.30	5.60	6.66	7.40		66	28.30	25.60	26.66	27.40	
			18	9.10	6.40	7.46	8.20		68	29.10	26.40	27.46	28.20	
			20	9.90	7.20	8.26	9.00		70	29.90	27.20	28.26	29.00	
			22	10.70	8.00	9.06	9.80		72	30.70	28.00	29.06	29.80	
			24	11.50	8.80	9.86	10.60	8.00	74	31.50	28.80	29.86	30.60	
			26	12.30	9.60	10.66	11.40		76	32.30	29.60	30.66	31.40	
			28	13.10	10.40	11.46	12.20		78	33.10	30.40	31.46	32.20	
			30	13.90	11.20	12.26	13.00		80	33.90	31.20	32.26	33.00	
			32	14.70	12.00	13.06	13.80		82	34.70	32.00	33.06	33.80	
			34	15.50	12.80	13.86	14.60		84	35.50	32.80	33.86	34.60	
			36	16.30	13.60	14.66	15.40		86	36.30	33.60	34.66	35.40	
			38	17.10	14.40	15.46	16.20		88	37.10	34.40	35.46	36.20	
			40	17.90	15.20	16.26	17.00		90	37.90	35.20	36.26	37.00	
			42	18.70	16.00	17.06	17.80		92	38.70	36.00	37.06	37.80	
			44	19.50	16.80	17.86	18.60	94	39.50	36.80	37.86	38.60		
			46	20.30	17.60	18.66	19.40	96	40.30	37.60	38.66	39.40		
			48	21.10	18.40	19.46	20.20	98	41.10	38.40	39.46	40.20		
			50	21.90	19.20	20.26	21.00	100	41.90	39.20	40.26	41.00		

**LXW** 连兴旺电子(深圳)有限公司  
connectivity LXWCONN ELECTRONICS (SHENZHEN) CO., LTD



一般公差 GENERAL TOLERANCE	制图 (DR):	品名(TITLE):
.X ±0.10	Kavin	0.8mm 双槽BTB SOCKET
.XX ±0.05	2016.07.05	
.XXX ±0.02	审核 (CHKD):	料号(PART NO):
ANGLES ±0°~30°		LB3XX-GxxS-B1R
修订 SER	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE
日期 DATE	版本 (REV)	比例(SCALE)
	C	1:8
		单位(UNITS)
		mm
		张数(SHEET)
		1 OF 1
		图幅(SIZE)
		A4