

Surge arrester

3-Electrode arrester

Series/Type: DG3R090M

Customer:

Version/Date: Issue 01/2013-11-02

Surge arrester

3-Electrode arrester

DG3R090M

Features	Applications
<ul style="list-style-type: none"> ● Extremely small size ● Extremely fast response time ● Stable performance over life ● Very low capacitance ● High insulation resistance ● RoHS-compatible ● UL Certification :E311500 	<ul style="list-style-type: none"> ● Splitter ● PCI Cards ● Morden ● Line Cards

Electrical specifications

DC breakdown voltage ¹⁾²⁾	90	V
Min.	72	V
Max.	108	V
Impulse breakdown voltage		
at 1kv/μs –For 99% measure values	≤600	V
Service life		
10 operations 8/20us	5	kA
300 operations 10/1000us	200	A
10 operations 50Hz,1S	5	A
Insulation resistance at DC 100V	≥1	GΩ
Capacitance at 1MHz	≤1.5	pF
Storage and operations temperature	-40...+90	°C
Climatic category (IEC60068-1)	40/90/21	
Marking,Blue positive	DG3R090M	



www.jsdgame.com


Surge arrester

3-Electrode arrester

DG3R090M


- 1) Sampling size in accordance to AQL0.65 II
 - 2) In ionized mode
 - 3) current from one side electrode to center electrode , and 2 times current through center electrode
- Tests according to ITU-T Rec. K. 12 IEC61663-2 and IEC61643-311

Dimensions



Tin-plated

Packaging 1000pce/reel



Cautions and warnings

- Surge arresters must not be operated directly in power supply networks, whose maximum operating voltage exceeds the minimum spark-over voltage of the surge arresters.
- Surge arresters may become hot in case of longer periods of current stress (danger of burning).
- If the contacts of the surge arrester are defective, current stress can lead to the formation of sparks and loud noise.
- Surge arresters may be used only within their specified values. In case of overload, the head contacts may fail or the component may be destroyed.
- Damaged surge arresters must not be re-used.

DC Elec.

Issue 01/2013-11-02