



($\phi 3.50\text{mm}$ DC PLUG DETAIL DRAWING)

- ### 主要技术性能
1. 额定电负荷: 30V 1.5A;
 2. 接触电阻: $\leq 0.03 \Omega$
 3. 绝缘电阻: $\geq 100M \Omega$
 4. 耐压: AC500V (50Hz) /min;
 5. 插拔力: 3~20N;
 6. 寿命: 5,000次。

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑥	GLUEWATER	—	1	—	BLACK	—
⑤	0型圈	—	1	氟橡胶	RED	—
④	COVER	—	1	PA66	BLACK	—
③	HOUSING	—	1	PA66	BLACK	—
②	PIN	—	1	BRASS	Gold Flash	—
①	CONTACT A	—	1	TAINLESS STEEL	Gold Flash	—

APPROVALS		DATE	TITLE:	
DRAWN	SUNNY	2020.5.29	DC POWER JACK	
CHECKED			ELECTRONICS CO.,LTD	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	PROJ:	SHEET
	A		NEW				30~以上 10~30 5~10 ~5	± 0.30 ± 0.25 ± 0.20 ± 0.15	mm	1:1	DC-118	1 OF 1