






linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	21.03.15



UL/CUL 技术参数 UL/CUL Technical Data						
等级 Use Group	B	C	D			
额定电压 Rated Voltage [V]	300	-	300			
额定电流 Rated Current [A]	8	-	10			
接线范围 Wire Range	-					
单/多芯线 Solid/Stranded [AWG]	-					
耐电压 Withstanding Voltage	1600V/1Min					
IEC 技术参数 IEC Technical Data						
过电压类别 Overvoltage Category	III	III	II			
污染等级 Contamination Class	-	2	2			
额定电压 Rated Voltage [V]	-	160	320			
额定电流 Rated Current [A]	-	7	7			
额定冲击电压 Impulse withstand voltage <sup>a</sup> [KV]	-	2.5	2.5			
导线截面积 Conductor cross section	-					
硬质/柔性导线 Solid/flexible [mm <sup>2</sup> ]	-					
材料 Material						
绝缘材料 Insulation Material	PA66					
阻燃等级 Imflammability	UL94V-0					
导体材料 Contactor Material	铜合金 Copper alloy					
导体表面镀层 Contactive Coating	镀锡 Tin Plated					
一般参数 Other Data						
间距 Pitch [mm]	3.5					
极数 Poles [P]	2-24					
剥线长度 Stripping Length [mm]	-					
螺丝 Screw/扭矩 Torque(Max) [N.m]	-					
工作温度 Operating temperatur [°C]	-40~+105					
引针尺寸 Pin Dimensions [mm]	-					
PCB板孔径 PCB Hole Diameter [mm]	-					

DES.	FZM	DATE	21.03.15	单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	A
CHK.	SY	DATE	21.03.15	慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD				名称/TITLE	KF2EDGWB-3.5			
APP.	CLF	DATE	21.03.15									