



1. Material:
 - Contaeis: Phosphone
 - Bronze
 - insulater: PBT+30%
 - G. F. UL 94V-0
 - Shell: SPCC
2. Mechanical:
 - Mating: 35N max.
 - Withdrowa Force: 10N min.
 - Darabirity: 1500 cycles min.
3. Elecetical:
 - Current-max (amps) 1.5A
 - Voitage-max (volls) 30V
 - Withstanding Voltage 750V AC
 - Contact Resistance (ohms) 30 milliohms max insulation
 - Resistance (ohms) 1000 Megogms min.
4. Plating:
 - Contacts: Gold And Tin Over
 - Nickel Ploled
 - Shell: Nickel over all plating.
5. Environmental:
 - temperature Range: -55 to 85 .

>0.5~2	±0.05	±0.10	±0.15	第一视角	设计	图面	A4	东莞市美韩电子科技有限公司			
>2~5	±0.15	±0.20	±0.25		Jack Jin	单位	MM	Dongguan Usakro Electronic Technology Co., Ltd.			
>5~10	±0.25	±0.28	±0.30		审核	比例		1:1	DWG NO.	型号: USB AF 侧插短体卷边	SIZE
角度 ANGLE		±0.5°			Jacky Zhong	重量		1 of 1	PART NO.	规格: 13.7*7.02*16.75	A4
未注尺寸公差 (mm)					批准	页码	1/1				
					Tony Meng	版次	A/0				R