



RECOMMEND PCB LAYOUT



1. Material:
  - Contacts: Phosphor Bronze
  - insulator: PBT+30%
  - G. F. UL 94V-0
  - Shell: SPCC
2. Mechanical:
  - Mating: 35N max.
  - Withdraw Force: 10N min.
  - Durability: 1500 cycles min.
3. Electrical:
  - Current-max (amps) 1.5A
  - Voltage-max (volts) 30V
  - Withstanding Voltage 750V AC
  - Contact Resistance (ohms) 30 milliohms max
  - insulation Resistance (ohms) 1000 Megohms min.
4. Plating:
  - Contacts: Gold And Tin Over Nickel Plated
  - Shell: Nickel over all plating.
5. Environmental:
  - temperature Range: -55 to 85 .

<b>产品图</b> MANUFACTURE FIG	<b>公差一览表</b> TOLERANCE TABLE		深圳市金航标电子有限公司	WWW.BDS666.COM
			KH-2AF180-10	0755-8344319
	<b>单位</b> UNIT	MM	INCH	<b>产品名称</b> PRODUCT NAME
	.X	±0.20	.X	±
	.XX	±0.10	.XX	±
	.XXX	±0.05	.XXX	±
	<b>2013.08.29</b>		<b>产品名称</b> PRODUCT NAME	USB A/F 双层直插10.0直边无脚
	<b>角法</b> ANGLE	⊕	<b>制图</b> DRAWING	<b>审核</b> CHECK
	<b>比例</b> SCALE	1:1	<b>设计</b> DESIGN	<b>批准</b> APPRO
	<b>版本</b> VERSION	A1	<b>图号</b> DRAWING NO.	CEC
			<b>图号</b> DRAWING NO.	第 1 / 1 页