




SCHOTTKY BARRIER RECTIFIERS

FEATURES

- Metal silicon junction, majority carrier conduction
- Guarding for overvoltage protection
- Low power loss, high efficiency
- High current capability
- low forward voltage drop
- High surge capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



MECHANICAL DATA

- Case: SOD-523
- Terminals: Solderable per MIL-STD-750, Method 2026

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Parameter	Symbols	B5817WT	B5818WT	B5819WT	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	V
Maximum RMS voltage	V_{RMS}	14	21	28	V
Maximum DC Blocking Voltage	V_{DC}	20	30	40	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1			A
Power dissipation	P_D	250			mW
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed On Rated Load (JEDEC method)	I_{FSM}	5			A
Maximum Instantaneous Forward Voltage at 1 A	V_F	0.45	0.55	0.6	V
Maximum Instantaneous Reverse Current at Rated DC Reverse Voltage $T_j = 25^{\circ}C$ $T_j = 100^{\circ}C$	I_R	1 10			mA
Thermal Resistance, Junction to Ambient Air (NOTE 1)	$R_{\theta JA}$	400			$^{\circ}C/W$
Typical Junction Capacitance $V_R=4V, f=1MHz$	C_j	120			pF
Storage and Operating Junction Temperature Range	T_j, T_{stg}	-55 ~ +125			$^{\circ}C$



Fig.1 Power Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 TYPICAL FORWARD VOLTAGE





Fig.4 Typical Junction Capacitance






PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SOD-523



UNIT		A	e	C	D	E	HE	N	L	P	<
mm	max	0.77	0.35	0.15	1.30	0.99	1.70	0.35	0.2	R0.1	10° ± 1°
	min	0.51	0.25	0.08	1.10	0.75	1.50	ref	ref	ALL ROUND	
mil	max	30	14	6	51	39	67	14	8.0	R4.0	
	min	20	10	3	43	30	59	ref	ref	ALL ROUND	

The recommended mounting pad size



Marking

Type number	Marking code
B5817WT	SJ
B5818WT	SK
B5819WT	SL



文件履历表

[illegible]