



Socket : RT-C14-M0B-AA
 1.Rating : 10A 250VAC VDE CCC
 15A 250VAC UL CUL
 2.Insulation resistance : >100MΩ Min 500VDC
 3.Dielectric strength : >2000VAC 1 minute
 Switch : SS21-BBIWF-S4-R
 1.Rating : 10A 125/250VAC UL CUL
 12(4)A 250V~ ENEC17;NEMKO;CQC;KC
 2.Contact resistance : <50mΩ
 3.Insulation resistance : >100MΩ (500VDC between open contacts)
 4.Dielectric strength : >1500VAC 0.5mA 1 minute

电话：0769-82310511-867
 邮箱：hooya89@hooya.hk

5	→	10	→	DIMENSIONAL TOLERANCES		APPROVED	CHECKED	DESIGN	DRAWN	ALL SIZE ARE IN	MM			
4	→	9	→	RANGE	TOLERANCE				LMC	SCALE	NO			
3	→	8	→	X	±0.30				2020.11.14	MAT'L	***	DRAWING NO.	REV.	
2	→	7	→	X.X	±0.20					MATERIAL NO.				
1	→	6	→	X.XX	±0.10							RT-C14-N1+SS21-6BB	*****	A0
NO	DESCRIPTION	NO	DESCRIPTION	ANGLES	±1'	LEGIION ELECTRONIC & HARDWARE CO., LTD.								