



NOTES:

1. MATERIAL SPECIFICATION
 - 1) INSULATION MATERIAL THERMOPLASTIC.
 - 2) SHELL: COPPER ALLOY/SPCC, T: 0.30mm
PLATING: NICKEL
 - 3) TERMINAL: COPPER ALLOY, T: 0.25mm
PLATING: GOLD/TIN PLATED.
 2. ELECTRICAL CHARACTERISTIC:
 - 1) INSULATION RESISTANCE: 1000MΩ MIN.
 - 2) CONTACT RESISTANCE: 30mΩ MAX.
 - 3) WITHSTANDING VOLTAGE: 500V AC.
 3. MECHANICAL CHARACTERISTICS:
 - 1) INSERTION FORCE: 3.57kgf MAX.
 - 2) EXTRACTION FORCE: 1.02kgf MIN.
- ORDERING INFORMATION

APPROVED:	DATE:	TITLE:	
CHECKED:	DATE:	USB-A/F-1*4P H=10.0mm 短体直插 鱼叉脚 卷边	
DRAWN:	DATE:	CLIENT P/N	SCALE
L. YUN	2019-09-08	/	free
TOLERANCE TABLE		FILE NO.	REV.
.0	±0.20	Ckmtw-USB-00134	A
.00	±0.15		
.000	±0.05		

深圳市灿科盟实业有限公司
CKM TW CHANKEMENG INDUSTRY CO., LTD

UNIT: /
SCALE: free
FILE NO.: Ckmtw-USB-00134
REV.: A