


SURFACE MOUNT ULTRAFAST RECOVERY RECTIFIER
Reverse Voltage - 50 to 1000 V
Forward Current - 1 A

FEATURES

- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- High efficiency
- Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- Case: SOD-123FL
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 15mg/0.00053oz

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

| Parameter | Symbols | U1A | U1B | U1D | U1G | U1J | U1K | U1M | Units | | | | | |
|--|-----------------|------------|-----|-----|-----|------|-----|------|---------|--|--|--|--|--|
| Maximum Repetitive Peak Reverse Voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | | | | | |
| Maximum RMS voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V | | | | | |
| Maximum DC Blocking Voltage | V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V | | | | | |
| Maximum Average Forward Rectified Current at $T_c = 100^\circ C$ | $I_{F(AV)}$ | 1 | | | | | | | A | | | | | |
| Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load | I_{FSM} | 30 | | | | | | | A | | | | | |
| Maximum Instantaneous Forward Voltage at 1 A | V_F | 1.0 | | 1.3 | | 1.70 | | V | | | | | | |
| Maximum DC Reverse Current $T_a = 25^\circ C$ at Rated DC Blocking Voltage $T_a = 125^\circ C$ | I_R | 5 100 | | | | | | | μA | | | | | |
| Maximum Reverse Recovery Time ⁽¹⁾ | t_{rr} | 50 | | | 75 | | | ns | | | | | | |
| Typical Junction Capacitance ⁽²⁾ | C_J | 15 | | | | | | | pF | | | | | |
| Typical Thermal Resistance ⁽³⁾ | $R_{\theta JA}$ | 85 | | | | | | | °C/W | | | | | |
| Operating and Storage Temperature Range | T_j, T_{stg} | -55 ~ +150 | | | | | | | °C | | | | | |

 (1) Measured with $I_F = 0.5 A$, $I_R = 1 A$, $I_{rr} = 0.25 A$.

(2) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(3) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristics






Fig.4 Maximum Non-Repetitive Peak Forward Surge Current




PACKAGE OUTLINE

Plastic surface mounted package; 2 leads



The recommended mounting pad size



Marking

| Type number | Marking code |
|-------------|--------------|
| U 1A | U 1A |
| U 1B | U 1B |
| U 1D | U 1D |
| U 1G | U 1G |
| U 1J | U 1J |
| U 1K | U 1K |
| U 1M | U 1M |