

Screw plug - A-EXSH-M32-68L-N-S - 1411109

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screw plug, cable gland material: Nickel-plated brass, Brass, nickel-plated, application: Ex, connecting thread: M32 x 1.5, color: silver



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	 4 046356 922241
GTIN	4046356922241
Weight per Piece (excluding packing)	90.000 g
Custom tariff number	74199990
Country of origin	United Kingdom

Technical data

Dimensions

Length	24 mm
Length without connecting thread	9 mm
Connecting thread diameter	32 mm
Thread pitch	1.5 mm
Wrench size, union nut	36 mm
Hexagon angular dimension	39.6 mm
Length of the connecting thread	15 mm

Ambient conditions

Degree of protection	IP66 (using the corresponding A-SEW-...P-W flat gasket)
----------------------	---

Screw plug - A-EXSH-M32-68L-N-S - 1411109

Technical data

Ambient conditions

	IP68 (using the corresponding A-SEW-...P-W flat gasket)
Ambient temperature (operation)	-60 °C ... 130 °C

General

Note	This item must only be used with counter nut 1411244 A-INL-M32-N-S for the Ex e type of protection.
Material	Brass, nickel-plated
Cable gland material	Nickel-plated brass
Thread type connection side	M32 x 1.5
Color	silver
Assembly instructions	Sealed to IP66/IP68 thanks to the use of the A-SEW-32-P-W flat gasket (item 1411285)
Standards/specifications	EN 60079-0, -1, -7
	IEC 60079-0, -1, -7
	EN 61241-0, -1
	IEC 61241-0, -1
Manufacturer	CMP
Manufacturer Designation	757DM4
Suited for EX-applications	yes

Standards and Regulations

Standards/regulations	EN 60079-0, -1, -7
	IEC 60079-0, -1, -7
	EN 61241-0, -1
	IEC 61241-0, -1
ATEX	Sira 01ATEX1284U
	Sira 02ATEX1003X
	Ex II 2 GD Ex d IIC & Ex e II, Ex IM2 Ex d I, Ex e I
IECEX	IECEX SIR 07.0056X
	Ex d I / Ex e I / Ex d IIC / Ex e II, Ex tD A21 IP6X


Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Screw plug - A-EXSH-M32-68L-N-S - 1411109

Dimensional drawing



Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	23111190
eCl@ss 9.0	23111190

ETIM

ETIM 4.0	EC000032
ETIM 5.0	EC000032
ETIM 6.0	EC000032

UNSPSC

UNSPSC 13.2	31161501
-------------	----------

Accessories

Accessories

Flat nut

Counter nut - A-INL-M32-N-S - 1411244



Counter nut, Brass, nickel-plated, for threads M32 x 1.5, color: silver

Seal

Screw plug - A-EXSH-M32-68L-N-S - 1411109

Accessories

Flat gasket - A-SEW-32-P-W - 1411285

Flat gasket, Nylon, for threads M32, color: white



Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>