


HSCMRRN001PDAA3

(Home : Products : TruStability® HSC)



TruStability® HSC Series-High Accuracy, ±1% total error band, analog, SMT, RR: dual radial barbed ports, same side, differential, ±1 psi, 3.3 Vdc, dry gases only, no special options

Actual product appearance may vary.

- M
- P
- S
- T
- S
- I
- S

[Sales & Service](#)

[Distributor Inventory](#)

[Overview](#)

[Specs](#)

[Documentation](#)

[Application Notes](#)

Product Specifications	
Measurement Type	Differential
Output	Analog
Signal Conditioning	Amplified
Pressure Range	±1 psi
Overpressure	10 psi
Supply Voltage	3.3 Vdc
Supply Current	1.6 mA typ.
Temperature Compensation	Yes
Output Calibration	Yes
Response Time	1 ms max.
Port Style	RR: dual radial barbed ports, same side
Package Type	SMT
Total Error (% Full Scale)	±1%
Accuracy (Best Fit Straight Line)	±0.25%
Shock	MIL-STD-202F, Method 213B, Condition F
Vibration	MIL-STD-202F, Curve AK (20.7 g random)
Operating Temperature	-20 °C to 85 °C [-4 °F to 185 °F]
Compensated Temperature Range	0 °C to 50 °C [32 °F to 122 °F]
Storage Temperature	-40 °C to 85 °C [-40 °F to 185 °F]
Media Compatibility	Dry gases only
Comment	No special options
Transfer Function	10% to 90% Vsupply

Product Specifications

Availability	Global
Series Name	TruStability® HSC

Product Search

Product Type:

Industry:

Search Term:

- New Products Only
- Entire Product Catalog

Search

My Links

- eCOM Login
- Request Access to eCOM
- Rep/AD Portal Login
- Rep/AD Portal Access Request
- Sample Request
- Digital University Login
- Limitless Microsite
- Supplier Microsite

Literature and Media

- Data Sheets
- Videos
- Literature
- Literature Request
- White Papers
- Application Notes
- Application Demos

Contact

- Custor
- Techni
- Global
- Websit



[Terms & Condi](#)