

6. INDICATED AREA SHALL BE CAPABLE OF MEETING THE SOLDERABILITY REQUIREMENTS OF 9-8825.

5. DIMENSIONS APPLY AFTER PLATING.

4. PLATE CONTACT BEFORE ASSEMBLY OF SLEEVE.

3. ADD LAST CHARACTER TO SUFFIX FOR FINISH:

SUFFIX FINISH

5 GOLD PLATE 9-7362-5

2. HOOD MUST BE PERMANENTLY RETAINED TO CONTACT BY CRIMPING. HOOD ROTATION OR LATERAL MOVEMENT NOT PERMISSIBLE AFTER CRIMPING. HOOD SHALL NOT PULL OFF WHEN SUBJECTED TO A 10 LB PULL.

1. A $\varnothing .0275^{+.0002}_{-.0000}$ HARDENED STEEL PIN SHALL ENGAGE SOCKET WITH A FORCE NOT GREATER THAN 7 OZ. FOLLOWING THIS A $\varnothing .0265^{+.0000}_{-.0002}$ HARDENED STEEL PIN SHALL DISENGAGE SOCKET WITH A FORCE NOT LESS THAN 1 OZ. PINS SHALL HAVE A $\sqrt{3}$ /FINISH AND A SPHERICAL END. INSERT PIN TO A DEPTH OF .138 MIN.

NOTES:

THE USE OF THIS DOCUMENT IS UNLIMITED.
HOWEVER, DOCUMENTS REFERENCED HEREON
MAY CONTAIN LIMITED RIGHTS DATA.

SIZE C	CAGE CODE 77820	DOCUMENT NO. 10-597982	REV. J
SCALE: 12.0		REF: 10-597980	SHEET 2 OF 2

SCALE: 12 0

REF:
10-597980

SHEET 2 OF 2