



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'HSEC4.02'

Your search criteria matched only one product, shown below

HSEC4.0-2



- Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
- Cross -linked UV resistant material improves chemical and temperature resistance
- Hot melt adhesive seals and insulates in one step to speed installation

	Part Number	HSEC4.02
	RoHS Compliancy Status	Compliant
	Part Description	Thick Wall End Caps provide protection for sealing ends of wire or cable
	Material	Polyolefin cross-linked with adhesive
	Color	Black
	Copper Conductor Size Range	#1500 - #2000 MCM
	Cap Length (In.)	6.9
	Cap Length (mm)	175.3
	Conductor Size Range (mm ²)	720 to 1000
	Max. Recovered I.D. (In.)	1.78
	Max. Recovered I.D. (mm)	45.2
	Min. Expanded I.D. (In.)	4.14
	Min. Expanded I.D. (mm)	105.2
	Nominal Recovered Wall Thickness (In.)	.150
	Nominal Recovered Wall Thickness (mm)	3.8
	Pricing Description	Heat Shrink Thick Adhesive End Cap, 4.1"(105mm)
	Shrink Ratio	3:1
	Temperature Range	-67°F to 221°F (-55°C to 105°C)
	Min. Order UOM	PC
	Min. Order Qty.	2
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.