


C44U, Film, Metallized Polypropylene, DC Link, 500 uF, 10%, 1100 VDC



General Information	
Supplier:	KEMET
Series:	C44U
Dielectric:	Metallized Polypropylene
Style:	Can
Features:	Standard Duty
RoHS:	Yes
Lead:	Threaded Studs M8
Miscellaneous:	Thermal Resistance = 3.4 C/W. Weight = 1120 grams

Dimensions	
D	85mm +/-1mm
L	174mm +/-2mm
S	31.7mm +/-0.2mm

Specifications	
Capacitance:	500 uF
Capacitance Tolerance:	10%
Voltage DC:	1100 VDC
Temperature Range:	-40/+85C
Rated Temperature:	75C
Max dV/dt:	12 V/us
Resistance:	1.1 mOhms (10kHz)
Ripple Current:	90 Amps (10kHz 40C), 6000 Amps (Peak)
Inductance:	80 nH

Packaging Specifications	
Mounting:	Bolt - M12x16
Packaging:	Bulk, Bag
Packaging Quantity:	5

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.