

## Sensor/Actuator cable - SAC-3P-M12MS/1,5-PUR/CI-1L-Z - 1400782

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/Actuator cable, 3-position, PUR, black-gray RAL 7021, Plug straight M12, A-coded, on Valve connector CI (9.4 mm), with 1 LED, connected with Z diode, connected with Z diode, Cable length: 1.5 m

As illustrated, but without SPEEDCON

RoHS

### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	0.070 g
Custom tariff number	85444290
Country of origin	Poland

### Technical data

#### Dimensions

Length of cable	1.5 m
-----------------	-------

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-20 °C ... 85 °C (valve plug)

#### General

Number of positions	3
Status display	1 LED
Protective circuit/component	Z diode
Insertion/withdrawal cycles	≥ 100

#### Cable

Cable type	PUR halogen-free black
Cable type (abbreviation)	PUR

## Sensor/Actuator cable - SAC-3P-M12MS/1,5-PUR/CI-1L-Z - 1400782

### Technical data


#### Cable

Cable abbreviation	Li9Y11Y-HF
UL AWM style	20549
Conductor cross section	3x 0.5 mm <sup>2</sup>
AWG signal line	20
Conductor structure signal line	28x 0.15 mm
Core diameter including insulation	1.5 mm ±0.05 mm (Signal line)
Wire colors	black 1, black 2, green/yellow
Overall twist	3 wires, twisted
External sheath, color	black-gray RAL 7021
External cable diameter D	4.5 mm ±0.2 mm
Smallest bending radius, fixed installation	22.5 mm
Number of bending cycles	15000000
Bending radius	50 mm
Traversing path	0.9 m
Traversing rate	5 m/s
Acceleration	30 m/s <sup>2</sup>
Outer sheath, material	PUR
Material conductor insulation	PP
Conductor material	Bare Cu litz wires
Insulation resistance	min. 20 MΩ*km
Conductor resistance	39 Ω/km (at 20 °C)
Nominal voltage, cable	≤ 300 V
Test voltage, cable	≥ 1200 V
Flame resistance	According to DIN VDE 0482
	According to DIN EN 50265-2-1
Halogen-free	in accordance with DIN VDE 0472 part 815
Other resistance	largely oil-resistant
	partly UV-resistant in accordance with DIN EN ISO 4892-2-A
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-20 °C ... 80 °C (cable, flexible installation)


### Drawings

# Sensor/Actuator cable - SAC-3P-M12MS/1,5-PUR/CI-1L-Z - 1400782

Schematic diagram



Cable cross section



PUR halogen-free black [PUR]

## Approvals

Approvals

---

Approvals

CSAus

---

Ex Approvals

---

## Approval details

CSAus <a href="http://www.csagroup.org/services/testing-and-certification/certified-product-listing/">http://www.csagroup.org/services/testing-and-certification/certified-product-listing/</a> 13631	
Nominal current I <sub>N</sub>	4 A
Nominal voltage U <sub>N</sub>	24 V

---