

Antenna - RAD-ISM-900-ANT-OMNI-RPSMA - 2885676

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Omni-directional antenna, IP55 protection, gain 2 dBi, linear vertical, RPSMA (male), impedance 50 Ω

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	54.43 g
Custom tariff number	85177019
Country of origin	United States

Technical data

Ambient conditions

Degree of protection	IP55
Ambient temperature (operation)	-20 °C ... 65 °C

General

Frequency range	900 MHz
	900 MHz
Horizontal beamwidth	360 °
Vertical beamwidth	NA
Impedance	50 Ω
Gain	2 dBi
Connection method	RSMA (male)

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	19070102
eCl@ss 5.1	19070102

Antenna - RAD-ISM-900-ANT-OMNI-RPSMA - 2885676

Classifications

eCl@ss

eCl@ss 6.0	19070102
eCl@ss 7.0	19070102
eCl@ss 8.0	19070105
eCl@ss 9.0	19070105

ETIM

ETIM 2.0	EC000416
ETIM 3.0	EC001698
ETIM 4.0	EC001698
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706