Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
- PDFH___X122H*T ..
- Specification Sheets
- PDF2-Sided Heat..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor



Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'H100X122H2T-2'**

**Your search criteria matched only one product, shown below**

## H100X122H2T-2

- Labels offer crisp, clear legends with superior legibility
- Meets UL Standard 224 for flammability and AMS -DTL-23053/5C (Class 1 and Class 3)
- Will meet MIL-M-81531, MIL-STD202F, and MIL-STD-883E when printed with RMH4BL or RHH4BL -S ribbons
- Shrink ratio 3:1
- Pre-cut flattened polyolefin is thermal transfer printable and supplied roll mounted on plastic carrier
- Panduit labeling software packages include all label formats for quick and easy label production

| | |
|---|---|
| Part Number | H100X122H2T-2 |
| RoHS Compliancy Status | Compliant |
| Part Description | 2-sided Military Grade printable heat shrink label, yellow, 3/4" (19.0mm) diameter polyolefin, 500/roll. |
| Material | 3:1 Flattened Polyolefin |
| Color | Yellow |
| Height (In.) | 1.22 |
| Height (mm) | 31.0 |
| Width (In.) | 1.00 |
| Width (mm) | 25.4 |
| Max. Wire O.D. (In.) | 0.13 |
| Max. Wire O.D. (mm) | 3.3 |
| Min. Cable O.D. (In.) | 0.04 |
| Min. Cable O.D. (mm) | 1.0 |
| Nominal Cable O.D. (In.) | 0.25 - 0.75 |
| Nominal Cable O.D. (mm) | 6.3 - 19.0 |
| Pricing Description | TT Heat Shrink 2Sided, .75" Diameter, Yellow |
| Min. Order UOM | RL |
| Min. Order Qty. | 1 |
| BOM Qty. (# of Pkgs.) | 0 |
| Add to Favorite Product List | e |

**Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.**


Copyright © 1995-2010, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy