




Home > Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

101TL2887-6



Actual product appearance may vary.

TL Series Toggle Switch, 1 pole, 2 position, IWTS (16-20 Gage) terminal, Special Design Lever

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

Features

Environmentproof sealing
 1,2, and 4 pole circuitry
 Standard and pull-to-unlock levers
 2 and 3 position, maintained and momentary toggle action
 Temperature range:-85° F to +160° F
 Completely sealed switching chamber
 Step-design case provides added space between terminals to help prevent shorting
 UL recognized, CSA certified
 CE approved

Potential Applications







Industrial machinery and equipment
 Military and commercial aviation
 Construction equipment
 Test instruments
 Agricultural machinery
 Process control
 Medical instrumentation

Description

MICRO SWITCH™ TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

- ▶ [Accessory: Lever Sleeve](#)
- ▶ [Accessory: Seals](#)
- ▶ [Accessory: Nuts](#)
- ▶ [Engineering Drawing](#)

Product Specifications							
Circuitry/Operating action	<table border="0"> <tr> <td style="text-align: center;">Keyway Momentary Position</td> <td style="text-align: center;">Opposite Keyway Position</td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td style="text-align: center;">1 2 ON</td> <td style="text-align: center;">1 2 OFF</td> </tr> </table>	Keyway Momentary Position	Opposite Keyway Position			1 2 ON	1 2 OFF
Keyway Momentary Position	Opposite Keyway Position						
							
1 2 ON	1 2 OFF						
Product Type	MICRO SWITCH™ Toggle Switch						
Ampere/Voltage Range (Resistive Load)	0.01 A to 0.1 A at 0.5 Vdc to 28 Vdc, 0.01 A to 0.1 A at 0.5 Vac to 115 Vac						
Circuitry	SPST						
Action	2 position						
Mounting	Bushing 15/32 in						
Termination	IWTS (16 -20 Gage)						
Lever Type	Special Design						
Comment	Gold Plated Contacts						
Availability	Global						
UNSPSC Code	30211908						
UNSPSC Commodity	30211908 Toggle switches						
Series Name	TL						

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search