



FFR.0S.405.CLAE33

MECHANICAL DETAILS

Shell Style Model FFR* : Straight plug for cable crimping with safety ring


Keying Circular (can rotate), plug has male contact(s)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing 2.6 - 3.3 mm

Variant 2 :

	A	L
Mm.	9	42
In.	0.35	1.65



Available Download

[high_voltage.pdf](#)

PERFORMANCE DETAIL

Insert 0S.405 : 1 High Voltage

Insulator L: PEEK

Specifications

Contact Type: Solder

OTHER CHARACTERISTICS

Endurance (Shell) Endurance (Shell):

Temp (min) -55°C

Temp (max) +250°C

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [6 ms]

Salt Spray >144 hr

Climatical 50/175/21

Shielding (min): 75 dB (10 MHz)

Shielding (min): 40 dB (1 GHz)

IP Rating 50



Related links

- [Contact](#)
- [Quote Request](#)
- [Catalogs Downloads](#)
- [Catalogs Requests](#)
- [Sample Request](#)
- [3D drawings](#)