

Technical data sheet · LÜTZE SUPERFLEX® N PUR



PUR C-track cable · For the highest requirements

Identification	Type	12×1.0
	Part-No.	101013

Use/Area of application

Application	<ul style="list-style-type: none">• Machine and device construction, transport and conveyor technology• Through full PUR jacket suited for c-tracks, extremely harsh operating conditions, aggressive coolants and lubricants• Special for industrial environments, machines and plants
Properties	<ul style="list-style-type: none">• Extreme space-saving design• Low capacitance, very good electrical properties• Halogen-free, no corrosive gases• Very good alternating bending strength• Low adhesion, abrasion-proof, nick-resistant, tear-propagation-resistant• hydrolysis-resistant, microbe-resistant, and rot-resistant• Weathering, ozone and UV resistant (normal lighting conditions)• Good industrial- and salt water resistance• Excellent coolant and lubricant resistance• Widely resistant to oils, greases, alcohol-free benzines and kerosene• Free from paint wetting disruptive substances (LABS-free), RoHS-compliant

Technical data

Voltage	U ₀ /U	300/500 V
Test voltage	3000 V	
Insulation resistance	min. 100 MΩ × km	
Temperature range	moving	-25 °C to +80 °C

23.11.2007 – Subject to technical modification

Part-No. 101013

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273
Tel.: +1 (704) 504-0222 · Fax: +1 (704) 504-0223
www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3 Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs, B77 4DU
Tel.: +44 (0)1827 31333-0 · Fax: +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk



Systematic Technology

Technical data sheet · LÜTZE SUPERFLEX® N PUR

Minimum bending radius	fixed moving	-40 °C to +80 °C Cable diameter × 10
Halogen-free	fixed according to DIN EN 50264-1; EN 50267-2-1; EN 60684-2	Cable diameter × 4
Number of strands/cross-section	12 × 1,0	
Outer-∅	9.3 approx. mm	
Weight	15.0 kg/100 m	
Cu-Index	11.9 kg/100 m	

Design

Conductor structure	Bare copper wire, finest multi-strand according to DIN VDE 0295 class 6, IEC 60228 class 6
Conductor insulation	Special-TPE conductor insulation
Conductor labelling	Conductors black with white number print according to DIN EN 50334
Ground conductor	green/yellow according to DIN EN 50334 in the top layer
Stranding	Conductors twisted without mechanical stress, layer pitch optimised
Banding	Non-woven material over stranded cable
Outer jacket	Full polyurethane jacket, matt, adhesion-free surface
Jacket colour	grey RAL 7001

General

Note	CE These products are in conformity to the EC Low Voltage Directive 73/23/EWG or 93/68/EWG respectively
------	---

Logo



halogenfree



low capacity

23.11.2007 – Subject to technical modification

Part-No. 101013

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273
Tel.: +1 (704) 504-0222 • Fax: +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3 Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs, B77 4DU
Tel.: +44 (0)1827 31333-0 • Fax: +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk