

Plug-in module - LDM-12-24DC - 2833686

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Plug-in module, for mounting on PR1 and PR2, with damping diode and yellow LED, polarity: A1-, A2+ (Japan standard), input voltage: 12 -24 V DC $\pm$ 20%

Why buy this product

- ☒ Mechanical keying to protect against mismatching
- ☒ Attenuation of reverse voltage induced in coil



Key commercial data

Packing unit	1
Minimum order quantity	10
Catalog page	Page 72 (IF-2011)
GTIN	 4 017918 933876
Custom tariff number	85366990
Country of origin	ITALY

Technical data

Product type	Plug-in module
Approval	UL Recognized
Approval	cUL Recognized
Approval	cULus Recognized
Design	PR1
Design	PR2
Input voltage	12 V DC ... 24 V DC

Classifications

ETIM

ETIM 2.0	EC001456
ETIM 3.0	EC001456
ETIM 4.0	EC001456

Plug-in module - LDM-12-24DC - 2833686

Classifications

ETIM

ETIM 5.0	EC001456
----------	----------

UNSPSC

UNSPSC 11	39121516
UNSPSC 12.01	39121516
UNSPSC 13.2	39121516
UNSPSC 6.01	30211917
UNSPSC 7.0901	39121516

eCl@ss

eCl@ss 4.0	27371190
eCl@ss 4.1	27371190
eCl@ss 5.0	27371692
eCl@ss 5.1	27371692
eCl@ss 6.0	27371603
eCl@ss 7.0	27371603

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 
--

cULus Recognized 
--

Plug-in module - LDM-12-24DC - 2833686

Drawings

Circuit diagram

