

HBL4715C -- Twist-Lock Flanged Receptacle



2P3W, 15A 125V, L5-15R, White Nylon

Product Specifications

Product Type



Product Item	Flanged Receptacle
Wiring Scheme	2-Pole, 3-Wire Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	L5-15R
Item Style	Standard
Device Color	White
Horsepower	0.5
Terminal Retainer Material	Clear polycarbonate
Terminal Clamp Material	.062" cold rolled steel-nickel-plated
Terminal Screw Material	#8-32 Brass (white finish on neutral screw when used)
Ground Screw Material	Brass (green finish)
Body Contact Carrier Material	Natural White Nylon
Contact Spring Material	Brass
Spring Binding Plate Material	Brass
Flanged Casing Material	Natural White Nylon
Mounting Screw Material	Nickel-plated Brass Round head screws
Ground Contact Material	.032" Bronze
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	15A #14 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Listings	UL/CSA
UPC Number	783585171005
Weight in LBs	0.05
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

