

I/O module - IB ST 24 DO16R/S - 2721112

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



INTERBUS-ST digital output module, 16 relay N/O contact outputs, 3-wire connection method, IP20 protection, consisting of: Terminal part with screw connection and module electronics

Product Description

INTERBUS ST digital output modules for AC voltages

The digital INTERBUS output modules are designed for the connection of digital actuators, such as electromechanical valves, contactors or lamps.

In addition to the standard IB ST 24 BDO modules, the range is rounded off by modules with extended functionality.

The scope of functions provided by the standard models covers the majority of applications. On top of this, several modules provide additional electronic functions, such as:

- Output channels in up to four electrically isolated groups
- Separate electronic short-circuit protection for each output channel
- Higher output current

which are needed in individual applications.

All the typical advantages of INTERBUS-ST handling, such as multi-wire connection methods and plug-in electronics are provided by both product lines.

Why buy this product

- 16 relay outputs
- Connection of actuators in 3-wire technology
- Floating relay contacts
- Diagnostic and status indicators



Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 132323
GTIN	4017918132323
Weight per Piece (excluding packing)	703.700 g
Custom tariff number	85389091
Country of origin	Germany

I/O module - IB ST 24 DO16R/S - 2721112

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	118 mm
Height	117 mm
Depth	116 mm

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Permissible humidity (operation)	75 % (non-condensing)
Permissible humidity (storage/transport)	95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	86 kPa ... 108 kPa (1500 m above sea level)
Degree of protection	IP20

Interfaces

Designation	ST local bus
Connection method	ST local bus connector
Transmission speed	500 kbps

Digital outputs

Output name	Relay output
Connection method	Screw connection
Connection technology	3-conductor
Number of outputs	16
Type of protection	Short-circuit protection
Nominal output voltage	230 V AC
Maximum output current per channel	3 A
Nominal load, inductive	200 VA
Nominal load, lamp	75 W
Nominal load, ohmic	750 W

Power supply for module electronics

Supply voltage	24 V DC
Supply voltage range	20 V DC ... 30 V DC (including ripple)
Ripple	3.6 V _{pp} within the allowable voltage range
Current consumption	100 mA

I/O module - IB ST 24 DO16R/S - 2721112

Technical data

General

Mounting type	DIN rail
Net weight	685 g

Electrical isolation

Test section	Main contact / N/O contact (per relay) 750 V AC 50 Hz 1 min.
	Contact / Contact (within a group) 1000 V AC 50 Hz 1 min.
	Group / Group 2000 V AC 50 Hz 1 min.
	Groups / 24 V 2000 V AC 50 Hz 1 min.
	Groups / 24 V 2000 V AC 50 Hz 1 min.
	24 V / PE 500 V AC 50 Hz 1 min.

Standards and Regulations

Connection in acc. with standard	CUL
Protection class	III, IEC 61140, EN 61140, VDE 0140-1

Classifications

eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250302
eCl@ss 5.0	27250302
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604
eCl@ss 9.0	27242604

ETIM

ETIM 2.0	EC001430
ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599
ETIM 6.0	EC001599

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404

I/O module - IB ST 24 DO16R/S - 2721112

Classifications

UNSPSC

UNSPSC 13.2	32151602
-------------	----------

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
---------------	---	---	---------------

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
----------------	---	---	---------------

EAC		EAC-Zulassung
-----	---	---------------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm
------------------	---	---

Accessories

Accessories

Bridge

I/O module - IB ST 24 DO16R/S - 2721112

Accessories

Jumper - IB ST LBC - 2836492



Spare local bus cable, for INTERBUS-ST modules

Insertion bridge - EB 84 IB ST BU - 2836269



Insertion bridges, divisible, isolated comb spine, color blue, 84-pos.

Insertion bridge - EB 84 IB ST RD - 2836272



Insertion bridges, divisible, isolated comb spine, color red, 84-pos.

Fuse

Fuse - IBS TR5 0,4AT - 2753478



Replacement fuse, for INTERBUS-ST modules

Replacement electronics module - IB STME 24 DO16R/S - 2721138



Replacement module electronics for IB ST (ZF) 24 DO 16 R/S

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>