

Power cable - PLD E 608-CA-MS/0,6/FS/UL - 2702307

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 3-position, PVC, gray RAL 7001, Plug straight, black, on Socket straight, black, cable length: 0.6 m, with UL approval

Product Description

The cable serves to connect multiple 600 class PLD enclosure lights in series.

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 113326
GTIN	4055626113326
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of cable	0.6 m
-----------------	-------

General

Rated current at 40°C	16 A
Rated voltage	250 V AC
Number of positions	3
Coding	black

Material

Material, knurls	not available
------------------	---------------

Power cable - PLD E 608-CA-MS/0,6/FS/UL - 2702307

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27378000
eCl@ss 4.1	27378000
eCl@ss 5.0	27379100
eCl@ss 5.1	27379100
eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 8.0	27279218
eCl@ss 9.0	27060311

ETIM

ETIM 5.0	EC002556
ETIM 6.0	EC001855
ETIM 7.0	EC001855

UNSPSC

UNSPSC 13.2	39131505
-------------	----------

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

UL Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 118976

Power cable - PLD E 608-CA-MS/0,6/FS/UL - 2702307

Approvals

cUL Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 118976

cULus Recognized



Accessories

Accessories

Power distributor

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.