


## Features

- Ultra High Efficiency (Up to 94.0%)
- Full Power at Wide Output Current Range (Constant Power)
- Thermal Sensing and Protection for LED Module
- DALI/Timer Dimmable (3 Timer Modes)
- Dim-to-Off with Standby Power  $\leq 0.5$  W
- Always-on Auxiliary Power: 12Vdc, 200mA
- Output Lumen Compensation
- Input Surge Protection: 6kV line-line, 10kV line-earth
- All-Around Protection: OVP, SCP, OTP
- Waterproof (IP67)
- SELV Output
- Suitable for Independent Use
- 7 Years Warranty



## Description






The EUD-320SxxxBV series is a 320W, constant-current, programmable LED driver that operates from 90-305 Vac input with excellent power factor. Created for many lighting applications including high bay, sports and horticultural, it provides a dim-to-off mode with low standby power. The high efficiency of these drivers and compact metal case enables them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, output over voltage, short circuit, and over temperature.

## Models

Adjustable Output Current Range	Full-Power Current Range (1)	Default Output Current	Input Voltage Range(2)	Output Voltage Range	Max. Output Power	Typical Efficiency (3)	Power Factor		Model Number
							120Vac	220Vac	
105-1500mA	1050-1500mA	1400 mA	90~305 Vac/ 127~250 Vdc	107~305Vdc	320 W	94.0%	0.99	0.96	EUD-320S150BV
154-2200mA	1540-2200mA	2100 mA	90~305 Vac/ 127~250 Vdc	73~208Vdc	320 W	93.5%	0.99	0.96	EUD-320S220BV
224-3200mA	2240-3200mA	2800 mA	90~305 Vac/ 127~250 Vdc	50~143Vdc	320 W	93.5%	0.99	0.96	EUD-320S320BV
322-4600mA	3220-4600mA	4200 mA	90~305 Vac/ 127~250 Vdc	35~100Vdc	320 W	93.5%	0.99	0.96	EUD-320S460BV <sup>(4)</sup>
469-6700mA	4690-6700mA	6700 mA	90~305 Vac/ 127~250 Vdc	24 ~ 68Vdc	320 W	93.5%	0.99	0.96	EUD-320S670BV <sup>(4)</sup>

- Notes:** (1) Output current range with constant power at 320W  
 (2) Certified voltage range: 100-240Vac or 127-250Vdc (except CCC and PSE)  
 (3) Measured at full load and 220Vac input (see below "General Specifications" for details).  
 (4) SELV Output

## I-V Operating Area



## Input Specifications

Parameter	Min.	Typ.	Max.	Notes
Input Voltage	90 Vac	-	305 Vac	127-250 Vdc
Input Frequency	47 Hz	-	63 Hz	
Leakage Current	-	-	0.70 mA	IEC60598-1; 240Vac/ 60Hz. grounding effectively
Input AC Current	-	-	3.30 A	Measured at full load and 120 Vac input.
	-	-	1.80 A	Measured at full load and 220 Vac input.
Inrush Current(I <sup>2</sup> t)	-	-	1.90 A <sup>2</sup> s	At 220Vac input, 25°C cold start, duration=3.52 ms, 10%Ipk-10%Ipk. See Inrush Current Waveform for the details.
PF	0.90	-	-	At 100-240Vac, 50-60Hz, 60%-100% Load (192-320W)
THD	-	-	20%	
THD	-	-	10%	At 220-240Vac, 50-60Hz, 75%-100% Load (240-320W)

## Output Specifications

Parameter	Min.	Typ.	Max.	Notes
Output Current Tolerance	-5%loset	-	5%loset	At full load condition
Output Current Setting(loset) Range				
EUD-320S150BV	105 mA	-	1500 mA	
EUD-320S220BV	154 mA	-	2200 mA	
EUD-320S320BV	224 mA	-	3200 mA	
EUD-320S460BV	322 mA	-	4600 mA	
EUD-320S670BV	469 mA	-	6700 mA	
Output Current Setting Range with Constant Power				
EUD-320S150BV	1050 mA	-	1500 mA	
EUD-320S220BV	1540 mA	-	2200 mA	
EUD-320S320BV	2240 mA	-	3200 mA	
EUD-320S460BV	3220 mA	-	4600 mA	
EUD-320S670BV	4690 mA	-	6700 mA	
Total Output Current Ripple (pk-pk)	-	5%lomax	10%lomax	At full load condition, 20 MHz BW
Output Current Ripple at < 200 Hz (pk-pk)	-	2%lomax	-	At full load condition. Only this component of ripple is associated with visible flicker.
Startup Overshoot Current	-	-	10%lomax	At full load condition
No Load Output Voltage				
EUD-320S150BV	-	-	350 V	
EUD-320S220BV	-	-	240 V	
EUD-320S320BV	-	-	160 V	
EUD-320S460BV	-	-	115 V	
EUD-320S670BV	-	-	78 V	
Line Regulation	-	-	±0.5%	Measured at full load
Load Regulation	-	-	±1.5%	

## Output Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Turn-on Delay Time	-	-	1.0 s	Measured at 120Vac input, 60%-100% Load.
	-	-	0.5 s	Measured at 220Vac input, 60%-100% Load.
Temperature Coefficient of I <sub>o</sub> set	-	0.03%/°C	-	Case temperature = 0°C ~T <sub>c</sub> max
12V Auxiliary Output Voltage	10.8 V	12 V	13.2 V	
12V Auxiliary Output Source Current	0 mA	-	200 mA	Return terminal is "OTP"

Note: All specifications are typical at 25°C unless otherwise stated.

## General Specifications

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 120 Vac input: EUD-320S150BV				Measured at full load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
I <sub>o</sub> =1050mA	89.5%	91.5%	-	
I <sub>o</sub> =1500mA	88.0%	90.0%	-	
EUD-320S220BV				
I <sub>o</sub> =1540mA	89.5%	91.5%	-	
I <sub>o</sub> =2200mA	88.5%	90.5%	-	
EUD-320S320BV				
I <sub>o</sub> =2240mA	89.5%	91.5%	-	
I <sub>o</sub> =3200mA	87.5%	89.5%	-	
EUD-320S460BV				
I <sub>o</sub> =3220mA	89.0%	91.0%	-	
I <sub>o</sub> =4600mA	87.5%	89.5%	-	
EUD-320S670BV				
I <sub>o</sub> =4690mA	89.0%	91.0%	-	
I <sub>o</sub> =6700mA	87.5%	89.5%	-	
Efficiency at 220 Vac input: EUD-320S150BV				Measured at full load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
I <sub>o</sub> =1050mA	92.0%	94.0%	-	
I <sub>o</sub> =1500mA	90.5%	92.5%	-	
EUD-320S220BV				
I <sub>o</sub> =1540mA	91.5%	93.5%	-	
I <sub>o</sub> =2200mA	90.5%	92.5%	-	
EUD-320S320BV				
I <sub>o</sub> =2240mA	91.5%	93.5%	-	
I <sub>o</sub> =3200mA	90.0%	92.0%	-	
EUD-320S460BV				
I <sub>o</sub> =3220mA	91.5%	93.5%	-	
I <sub>o</sub> =4600mA	90.0%	92.0%	-	
EUD-320S670BV				
I <sub>o</sub> =4690mA	91.5%	93.5%	-	
I <sub>o</sub> =6700mA	89.5%	91.5%	-	

## General Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 277 Vac input: EUD-320S150BV Io=1050mA Io=1500mA EUD-320S220BV Io=1540mA Io=2200mA EUD-320S320BV Io=2240mA Io=3200mA EUD-320S460BV Io=3220mA Io=4600mA EUD-320S670BV Io=4690mA Io=6700mA	92.0% 91.0% 92.0% 90.5% 92.0% 90.0% 91.5% 90.5% 91.5% 90.0%	94.0% 93.0% 94.0% 92.5% 94.0% 92.0% 93.5% 92.5% 93.5% 92.0%	- - - - - - - - - -	Measured at full load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
Standby power	-	-	0.5 W	Measured at 230Vac/50Hz; Dimming off
MTBF	-	237,000 Hours	-	Measured at 220Vac input, 80%Load and 25°C ambient temperature (MIL-HDBK-217F)
Lifetime	-	97,000 Hours	-	Measured at 220Vac input, 80%Load and 70°C case temperature; See lifetime vs. Tc curve for the details
Operating Case Temperature for Safety Tc_s	-40°C	-	+89°C	
Operating Case Temperature for Warranty Tc_w	-40°C	-	+75°C	Case temperature for 7 years warranty. Please see <i>Inventronics Warranty Statement for complete details.</i>
Storage Temperature	-40°C	-	+85°C	Humidity: 5%RH to 100%RH
Dimensions Inches (L x W x H) Millimeters (L x W x H)	8.86 x 3.86 x 1.77 225 x 98 x 44.8			With mounting ear 9.88 x 3.86 x 1.77 251 x 98 x 44.8
Net Weight	-	1875 g	-	

**Note:** All specifications are typical at 25°C unless otherwise stated.

## Dimming Specifications

Parameter	Min.	Typ.	Max.	Notes
DA, DA High Level	9.5V	16V	22.5V	
DA, DA Low Level	-6.5V	0V	6.5V	
DA, DA Current	0mA	-	2mA	

## Dimming Specifications (Continued)

Parameter		Min.	Typ.	Max.	Notes
Dimming Output Range	EUD-320S150BV EUD-320S220BV EUD-320S320BV EUD-320S460BV EUD-320S670BV	10%I <sub>load</sub>	-	I <sub>load</sub>	1050mA ≤ I <sub>load</sub> ≤ 1500mA 1540mA ≤ I <sub>load</sub> ≤ 2200mA 2240mA ≤ I <sub>load</sub> ≤ 3200mA 3220mA ≤ I <sub>load</sub> ≤ 4600mA 4690mA ≤ I <sub>load</sub> ≤ 6700mA
	EUD-320S150BV EUD-320S220BV EUD-320S320BV EUD-320S460BV EUD-320S670BV	105mA 154mA 224mA 322mA 469mA	-	I <sub>load</sub>	105mA ≤ I <sub>load</sub> < 1050mA 154mA ≤ I <sub>load</sub> < 1540mA 224mA ≤ I <sub>load</sub> < 2240mA 322mA ≤ I <sub>load</sub> < 3220mA 469mA ≤ I <sub>load</sub> < 4690mA

**Note:** All specifications are typical at 25 °C unless stated otherwise.

## Standards Compliance


Safety Category	Standard
CE	EN 61347-1, EN61347-2-13
EMI Standards	Notes
EN 55015 <sup>(1)</sup>	Conducted emission Test & Radiated emission Test
EN 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
EMS Standards	Notes
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: line to line 6 kV, line to earth 10 kV <sup>(2)</sup>
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment
DALI Standards	Notes
DALI	IEC62386-101,102 & part of 207 <sup>(3)</sup>

**Note:** (1) This LED driver meets the EMI specifications above, but EMI performance of a luminaire that contains it depends also on the other devices connected to the driver and on the fixture itself.


(2) To perform electric strength (hi-pot) testing, the “GDT ground disconnect” (nut and metal lock sheet) on the driver end-cap should be removed temporarily to prevent the internal gas discharge tube from conducting (as allowed by IEC 60598-1 Clause 10.2). After testing is completed, these items must be reinstalled to restore line-to-earth surge protection and secure the end cap.

(3) Optional Commands Implemented: 242 (query short circuit), 243 (query open circuit)


## Derating









## Lifetime vs. Case Temperature







## Inrush Current Waveform




## Efficiency vs. Load








## Power Factor



## Total Harmonic Distortion




## Protection Functions


Parameter		Min.	Typ.	Max.	Notes
External Thermal Protection NTC	R1	-	7.81 kOhm	-	When R_NTC falls below R1, External Thermal Protection is triggered, reducing output current until R2 is reached.
	R2	-	4.16 kOhm	-	When R_NTC is less than R2, output current is reduced to the programmed "Protection Current Floor."
	Protection Current Floor	10%loset	60%loset	100%loset	10%loset > Iomin (default setting is 60%)
		Iomin	60%loset	100%loset	10%loset ≤ Iomin (default setting is 60%)
Over Temperature Protection		Decreases output current, returning to normal after over temperature is removed.			
Short Circuit Protection		Auto Recovery. No damage will occur when any output is short circuited. The output shall return to normal when the fault condition is removed.			
Over Voltage Protection		Limits output voltage at no load and in case the normal voltage limit fails.			

## Dimming

### ● DALI Dimming

The recommended implementation of the dimming control is provided below.





Implementation: DALI Dimming

● **Time Dimming**


Time dimming control includes 3 kinds of modes, they are Self Adapting-Midnight, Self Adapting-Percentage and Traditional Timer.

- **Self Adapting-Midnight:** Automatically adjusts the dimming curve based on the on-time of past two days (if difference <15 minutes), assuming that the center point of the dimming curve is midnight local time.
- **Self Adapting-Percentage:** Automatically adjusts the on-time of each step by a constant percentage = (actual on-time for the past 2 days if difference <15 min) / (programmed on-time from the dimming curve).
- **Traditional Timer:** Follows the programmed timing curve after power on with no changes.

● **Output Lumen Compensation**

Output Lumen Compensation (OLC) may be used to maintain constant light output over the life of the LEDs by driving them at a reduced current when new, then gradually increasing the drive current over time to counteract LED lumen degradation.


**Programming Connection Diagram**



- Note:** (1) The driver does not need to be powered on during the programming process.  
 (2) Both "OTP-" and "DA" (gray) should be connected to "Return" of the programmer when programming.

● Please refer to [PRG-MUL2 \(Programmer\)](#) datasheet for details.

## Mechanical Outline



## RoHS Compliance

Our products comply with the European Directive 2011/65/EC, calling for the elimination of lead and other hazardous substances from electronic products.

## Revision History

Change Date	Rev.	Description of Change		
		Item	From	To
2017-05-09	A	Datasheets Release	/	/
2017-10-25	B	Features	7 Years Warranty	Added
		Input Specifications	PF/THD	Updated
		General Specifications	Operating Case Temperature for Warranty Tc_w	Updated
2018-01-22	C	Description	/	Updated
		General Specifications	Lifetime	Updated
		Operating Case Temperature for Warranty Tc_w	+70°C	+75°C
		Lifetime vs. Case Temperature	/	Updated