

# HBL5284 -- Straight Blade Products, Panel Mount Receptacle



2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Panel mount on 1.94" (49.3) Centers, Brown

## Product Specifications

Product Type	<p>Panel Mount Devices</p>
Receptacle Style	Single
Face Shape	Traditional
Standard	NEMA
Amperage	15A
Voltage	125V
Poles and Wires	2 Pole, 3-Wire Grounding
Hospital Grade ?	No
Panel Mounting Dimension	Panel Mount 1.94" ctrs.
Receptacle Grade	Heavy Duty Spec Grade
Face Style	Finder Groove
Color	<p>Brown</p>
NEMA No.	5-15R
Horsepower	0.5
Type	2 Pole, 3 Wire, Grounding
Rating	15A, 125V
Certification	UL Listed File E2186, Guide Fed. Spec. WC 596F, Listed to UL Standard 498. Certified to CSA 22.2, No. 42 where applicable.
Terminal Screw Material	#8-32 Brass /Ni plated for neutral
Ground Screw Material	#8-32 Brass, Multiple Drive (Green)
Top Material	Nylon
Base Material	Reinforced PET
Power Contacts Material	.040" (1.0) Brass
Mounting Strap Material	.050" (1.3) Brass
Mounting Screw Material	Steel-Zinc Plated
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#14-#10 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 V2.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585014227
Weight in LBs	0.200
Link to Drawing Library	<a href="#">Click here for Library</a>
Link to PDF Catalog	<a href="#">Click here for Catalog</a>

