



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#)

Text Search: 'H100X084H3T'

Your search criteria matched only one product, shown below

H100X084H3T



- Labels offer crisp, clear legends with superior legibility
- Meets UL Standard 224 for flammability and AMS -DTL-23053/5C (Class 1 and Class 3)
- Will meet MIL-M-81531, MIL-STD202F, and MIL-STD-883E when printed with RMH4BL or RHH4BL-S ribbons
- Shrink ratio 3:1
- Pre-cut flattened polyolefin is both thermal transfer and dot matrix printable and supplied roll mounted on plastic carrier
- *PANDUIT* labeling software packages include all label formats for quick and easy label production

	Part Number	H100X084H3T
	RoHS Compliancy Status	Compliant
	Part Description	Black, 1/2" diameter polyolefin, 1000/roll.
	Material	3:1 Flattened Polyolefin
	Color	Black
	Length (In.)	.84
	Length (mm)	21.34
	Width (In.)	1.00
	Width (mm)	25.40
	Max. Wire O.D. (In.)	.50
	Max. Wire O.D. (mm)	12.70
	Min. Cable O.D. (In.)	.17
	Min. Cable O.D. (mm)	4.32
	Nominal Cable O.D. (In.)	.17 - .50
	Nominal Cable O.D. (mm)	4.32 - 12.70
	Pricing Description	Heat Shrink Label, 0.50" (12.7mm) Dia., Black
	Min. Order UOM	RL
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.