



Relays & Contactors > Relays > Power Relays



Relay Type: **Standard**
Coil Magnetic System: **Monostable, DC**
Coil Power Rating DC: **500 mW**
Coil Resistance: **270 Ω**
Coil Voltage Rating: **12 VDC**

Features

Product Type Features

Relay Type	Standard
------------	----------

Electrical Characteristics

Insulation Initial Dielectric Between Coil & Contact Class	4000 V
Coil Current	.044 A
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Coil Power Rating	.5 W
Contact Limiting Continuous Current	8 A
Insulation Creepage Class	8 mm
Coil Power Rating Class	500 – 600 mW
Insulation Initial Dielectric Between Adjacent Contacts	2500 Vrms
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
Insulation Creepage Between Contact & Coil	8 mm[.315 in]
Coil Magnetic System	Monostable, DC
Coil Power Rating DC	500 mW
Coil Resistance	270 Ω
Coil Voltage Rating	12 VDC
Contact Switching Voltage (Max)	400 VAC
Contact Voltage Rating	250 VAC



Body Features

Product Weight	18 g[.635 oz]
----------------	---------------

Contact Features

Contact Plating Material	Silver-Nickel Gold Covered
Contact Arrangement	2 Form C (CO)
Contact Current Class	5 – 10 A
Contact Current Rating	8 A
Contact Material	AgNi0.15, Silver-Nickel Gold Covered
Contact Number of Poles	2

Termination Features

Relay Connection Type	PCB Termination
Terminal Configuration	Solder Pins

Mechanical Attachment

Product Mount Type	Printed Circuit Board
--------------------	-----------------------

Dimensions

Length Class (Mechanical)	25 – 30 mm
Insulation Clearance Class	8 mm
Height Class (Mechanical)	25 – 30 mm
Insulation Clearance Between Contact & Coil	8 mm[.315 in]
Width Class (Mechanical)	12 – 16 mm
Product Width	12.6 mm[.496 in]
Product Length	29 mm[1.14 in]
Product Height	25.5 mm[1 in]

Usage Conditions

Environmental Ambient Temperature Class	-40 – 70 °C
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operating Temperature Range	-40 – 70 °C[-40 – 158 °F]

Packaging Features

Packaging Method	Box & Tube
------------------	------------

Other

Solder Process	Wave Solder
----------------	-------------



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6-trimethylphenyl)- (2% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1393161-9
RP28500-RETAINING CLIP



TE Part # 1-1393845-0
RP821F12



TE Part # 1860996-1
RP16C01 PLASTIC RETAINING CLIP
HIGH



TE Part # 1860991-1
RT78602, RELAY SOCKET PCB 5MM
HIGH

Customers Also Bought



TE Part #1623728-4
BCHE 11 W 150R 5%

TE Part #1623819-9
SBL4 R022 5%

TE Part #1-292254-4
CT RELAY HDR ASSY 14P NAT

TE Part #1-1623819-2
SBL4 R047 5%

TE Part #194781-E
M12 FEMALE, A CODE, 5P, 17MM
SMT

Documents

CAD Files

Customer View Model

[ENG_CVM_1393845-4_SFB1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_1393845-4_SFB1.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_1393845-4_SFB1.2d_dxf.zip](#)

English

3D PDF

English

Customer View Model

[ENG_CVM_CVM_1393845-4_A1.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1393845-4_A1.3d_igs.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1393845-4_A1.2d_dxf.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[PCB Accessories Industrial Power Relays](#)



English

[Power PCB Relay RPII/2](#)

English

[Product Specifications](#)

[Definitions General Purpose Relays](#)

English

[Agency Approvals](#)

[VDE Certificate](#)

English