



Specifications:
 规格:
 Voltage rating:600V AC/DC
 额定电压: 600V AC/DC
 Withstanding voltage:2500V AC/minute
 耐受电压: 2500V AC/分钟
 Temperature range:-40°C-+125°C
 温度范围: -40°C-+125°C
 Insulation resistance:1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:5mΩ Max
 接触电阻: 5mΩ Max

K 792100 T - P XX - X
 ① ② ③ ④ ⑤ ⑥

- 1.K: XKBTEK-Car Connector
- 2.XKB Series No
- 3.Category:T-Terminal
- 4.Material:P-Phosphor Bronze
- 5.Plating:SN-Tin Plated over Nickel
V01-Gold Flash ;AuSn-Terminal half-AuSn
- 6.Special No:H-High foot ;L-Low foot



SEC: A-A



SEC: B-B

K792100T-PXX-H	7.00	6.80	6.80	5.60
K792100T-PXX-L	4.40	5.20	3.90	4.00
PART NO	DIM A	DIM B	DIM C	DIM D

Poles	10 AWG	12 AWG	14 AWG	16 AWG
01	30 A	25 A	20 A	15 A
02	25 A	20 A	18 A	15 A
03	25 A	20 A	18 A	15 A
04	22 A	18 A	15 A	13 A
05	22 A	18 A	15 A	13 A

K792100T-PXX-H	Phosphor Bronze	AWG#10~12	K792100H
K792100T-PXX-L		AWG#14~16	
PART NO	Material	Wire Range	Suitable XKB Housing

DSND	SCALE: N/A	MODEL TYPE: 7.92mm Automobile connector
DWN	VIEW:	PART NO.: K792100T-PXX-X
CHKD	UNIT: mm/in	DWG NO.: X-K792100T-PXX-X
APPD	SIZE: A4	WEIGHT SHEET REVISION 1/1 A0

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	



XKB INDUSTRIAL PRECISION CO., LIMITED