





linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		GLF	21.03.15



UL/CUL 技术参数 UL/CUL Technical Data					
等级	Use Group		B	C	D
额定电压	Rated Voltage [V]		600	600	600
额定电流	Rated Current [A]		41	41	5
接线范围	Wire Range		24-8		
单/多芯线	Solid/Stranded [AWG]				
耐电压	Withstanding Voltage		2200V/1Min		
IEC 技术参数 IEC Technical Data					
过电压类别	Overtoltage Category		III	III	II
污染等级	Contamination Class		-	2	2
额定电压	Rated Voltage [V]		-	1000	1000
额定电流	Rated Current [A]		-	41	41
额定冲击电压	Impulse withstand voltage <sup>a</sup> [KV]		-	8.0	6.0
导线截面积	Conductor cross section		6.0		
硬质/柔性导线	Solid/flexible [mm <sup>2</sup> ]				
材料 Material					
绝缘材料	Insulation Material		PA66		
阻燃等级	Imflammability		UL94V-0		
导体材料	Contactur Material		铜合金 Copper alloy		
导体表面镀层	Contactive Coating		镀镍 Ni plated		
一般参数 Other Data					
间距	Pitch [mm]		7.62		
极数	Poles [P]		2-16		
剥线长度	Stripping Length [mm]		7-8		
螺丝	Screw/扭矩 Torque(Max) [N.m]		M3/0.5		
工作温度	Operating temperatur [°C]		-40~+105		
引针尺寸	Pin Dimensions [mm]		-		
PCB板孔径	PCB Hole Diameter [mm]		-		

DES.	FZM	DATE	21.03.15	单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	A
CHK.	SY	DATE	21.03.15	慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD				名称/TITLE	KF2EDGSKTM-7.62			
APP.	CLF	DATE	21.03.15									