

## Front adapters - FLKM S135/S400/SO126 - 2301781

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid  
(<http://phoenixcontact.com/download>)



The FLKM S135/S400/SO adapter links a SIMATIC® S5 plug directly with the basic SIMATIC® S7 400 card.  
Conversion: S5 card 6ES5 451-4UA14 to S7 card 6ES7-422-1BL00-0AA0

RoHS

### Key Commercial Data

|                                      |                                                                                      |
|--------------------------------------|--------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                 |
| GTIN                                 |  |
| GTIN                                 | 4017918954598                                                                        |
| Weight per Piece (excluding packing) | 352.500 g                                                                            |
| Custom tariff number                 | 85369010                                                                             |
| Country of origin                    | Germany                                                                              |

### Technical data

#### Note

|              |                                           |
|--------------|-------------------------------------------|
| Type of note | Notes on operation                        |
| Note         | The LEDs of the S7-400 module are hidden. |

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Degree of protection                    | IP00             |

#### General

|                                    |                                                        |
|------------------------------------|--------------------------------------------------------|
| Max. permissible operating voltage | 60 V DC                                                |
| Max. permissible current           | 4 A (per path)                                         |
|                                    | 4 A (per connection, supply via separate power supply) |

## Front adapters - FLKM S135/S400/SO126 - 2301781

### Technical data

#### General

|                   |     |
|-------------------|-----|
| Mounting position | any |
|-------------------|-----|

#### Connection data

|                   |                            |
|-------------------|----------------------------|
| Connection name   | Field level                |
| Connection method | SIEMENS S5-135 U pin strip |

#### Supported controller


|                     |                     |
|---------------------|---------------------|
| Controller          | SIEMENS S5-135 U    |
| - suitable I/O card | 6ES5 451-4UA14      |
| Controller          | SIEMENS S7-400      |
| - suitable I/O card | 6ES7 422-1BL00-0AA0 |

#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Drawings

Circuit diagram



Connection scheme: FLKM S135/S400/SO126

## Front adapters - FLKM S135/S400/SO126 - 2301781

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27242292 |
| eCl@ss 4.0    | 27250300 |
| eCl@ss 4.1    | 27250300 |
| eCl@ss 5.0    | 27250300 |
| eCl@ss 5.1    | 27250300 |
| eCl@ss 6.0    | 27249200 |
| eCl@ss 7.0    | 27249290 |
| eCl@ss 8.0    | 27249290 |
| eCl@ss 9.0    | 27242292 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002584 |
| ETIM 5.0 | EC002584 |
| ETIM 6.0 | EC002584 |
| ETIM 7.0 | EC002584 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211824 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11     | 39121421 |
| UNSPSC 12.01  | 39121421 |
| UNSPSC 13.2   | 32151601 |
| UNSPSC 18.0   | 32151601 |
| UNSPSC 19.0   | 32151601 |
| UNSPSC 20.0   | 32151601 |
| UNSPSC 21.0   | 32151601 |

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

---

# Front adapters - FLKM S135/S400/SO126 - 2301781

## Approvals

### Approval details

|     |                                                                                   |                          |
|-----|-----------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.A*30.B.01742 |
|-----|-----------------------------------------------------------------------------------|--------------------------|