


Twist-Lock® Devices
30 Ampere, 3Ø Y 120/208, 277/480 and 347/600 Volts AC
 4 Pole, 4 Wire Non-Grounding
Insulgrip® Plugs, Flanged Inlets, Connector Bodies and Receptacles




HBL2751




HBL2755



HBL2753



HBL2750



HBL2756

IP20
SUITABILITY



30A 3ØY
120/208V AC
NEMA L18-30P
UL Listed
3 HP



30A 3ØY
277/480V AC
NEMA L19-30P
UL Listed
10 HP



30A 3ØY
347/600V AC
NEMA L20-30P
UL Listed

Plugs

Description	Cord Dia.	Catalog Numbers		
Black and white nylon.	.35"-1.15" (9-29)	HBL2751	HBL2761	HBL2771

Accessories on page B-53.

Flanged Inlets

Description	Catalog Numbers		
Nylon casing, back wired.	HBL2755	HBL2765	HBL2775

Accessories on page B-52.

IP20
SUITABILITY



30A 3ØY
120/208V AC
NEMA L18-30R
UL Listed
3 HP



30A 3ØY
277/480V AC
NEMA L19-30R
UL Listed
10 HP



30A 3ØY
347/600V AC
NEMA L20-30R
UL Listed

Connector Bodies

Description	Cord Dia.	Catalog Numbers		
Black and white nylon.	.35"-1.15" (9-29)	HBL2753	HBL2763	HBL2773

Accessories on page B-53.

Single Flush Receptacles, Back and Side Wired

Description	Catalog Numbers		
Black nylon face.	HBL2750	HBL2760	HBL2770

Accessories on page B-52.

Flanged Receptacles

Description	Catalog Numbers		
Nylon casing, back wired.	HBL2756	HBL2766	HBL2776

Accessories on page B-52.

Note: For technical information on Twist-Lock® Devices see page B-69.