

Inline function terminal - IB IL TEMPCON UTH-PAC - 2861807

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline temperature regulators, complete with accessories (connector and labeling field), 8 inputs for thermocouples, 8 outputs, 24 V DC, 2-wire connection method

Product Features

- 8 analog inputs for thermocouples
- 8 outputs, 24 V DC, 70 mA
- Can be configured as a 2-step controller, 3-step controller, motor step controller or signaling device (threshold value switch)
- Self-tuning
- Heating current and closed-loop control circuit monitoring
- Configuration via engineering tool (configuration software)



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	222.6 g
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm

Ambient conditions

Degree of protection	IP20
----------------------	------

Inline function terminal - IB IL TEMPCON UTH-PAC - 2861807

Technical data

Interfaces

Interface	Inline local bus
Connection method	Inline data jumper
Transmission speed	500 kBit/s

Power supply

Communications power U_L	7.5 V DC (via voltage jumper)
Typical current consumption	250 mA
Max. current consumption	4 A

Electrical isolation

Test section	5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	24 V supply (I/O) / functional earth ground 500 V AC 50 Hz 1 min.
	Analog inputs/bus logics 500 V AC 50 Hz 1 min.
	Analog inputs/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	Analog inputs/functional earth ground 500 V AC 50 Hz 1 min.

Inputs

Number of inputs	8
Connection method	2-wire
Measured value representation	Depends on thermocouple
Measured value resolution	0.1 K
A/D conversion time	approx. 70 ms

General

Weight	122 g
Number of plugs	4
Mounting type	DIN rail
Designation	Inline connector
Connection method	Spring-cage connection
Conductor cross section solid min.	0.08 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section flexible min.	0.08 mm ²
Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG min.	28
Conductor cross section AWG max.	16
Connection method	2-wire (shielded)

Inline function terminal - IB IL TEMPCON UTH-PAC - 2861807

Technical data

Outputs

Number of outputs	8
Connection method	2-wire (shielded)
Output voltage	24 V DC
Output current	70 mA

Inline potentials

Communications power U_L	7.5 V
Current consumption from U_L	max. 250 mA
	typ. 90 mA
Segment circuit supply U_S	24 V DC (nominal value)
Current consumption from U_S	max. 0.6 A
Current consumption from U_{ANA}	typ. 20 mA

Standards and Regulations

Test section	5 V supply, incoming remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	5 V supply, outgoing remote bus/7.5 V supply (bus logics) 500 V AC 50 Hz 1 min.
	7.5 V supply (bus logics)/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	24 V supply (I/O) / functional earth ground 500 V AC 50 Hz 1 min.
	Analog inputs/bus logics 500 V AC 50 Hz 1 min.
	Analog inputs/24 V supply (I/O) 500 V AC 50 Hz 1 min.
	Analog inputs/functional earth ground 500 V AC 50 Hz 1 min.
Connection in acc. with standard	CUL

Classifications

eCl@ss

eCl@ss 4.0	27250304
eCl@ss 4.1	27250304
eCl@ss 5.0	27250304
eCl@ss 5.1	27242605
eCl@ss 6.0	27242605
eCl@ss 7.0	27242605

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601

Inline function terminal - IB IL TEMPCON UTH-PAC - 2861807

Classifications

ETIM


ETIM 5.0	EC001601
----------	----------

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Drawings

Connection diagram



Dimensional drawing

