



**SPECIFICATIONS**

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

| 编 号         | 尺寸 (mm) |       |
|-------------|---------|-------|
|             | A       | B     |
| A2508-2X04Y | 7.50    | 15.00 |
| A2508-2X05Y | 10.00   | 17.50 |
| A2508-2X06Y | 12.50   | 20.00 |
| A2508-2X07Y | 15.00   | 22.50 |
| A2508-2X08Y | 17.50   | 25.00 |
| A2508-2X09Y | 20.00   | 27.50 |
| A2508-2X10Y | 22.50   | 30.00 |
| A2508-2X11Y | 25.00   | 32.50 |
| A2508-2X12Y | 27.50   | 25.00 |
| A2508-2X13Y | 30.00   | 37.50 |
| A2508-2X14Y | 32.50   | 40.00 |
| A2508-2X20Y | 47.50   | 55.00 |

|                   |            |          |            |       |           |                |  |                     |     |
|-------------------|------------|----------|------------|-------|-----------|----------------|--|---------------------|-----|
| GENERAL TOLERANCE |            | 制图       | 钱岳生        |       | 料号        | A2508-2XNY     |  | 版本                  | A   |
| X.±0.25           | X.*±2'     | DRAWING  | 2013、07、01 |       | PART NO.  |                |  | REV.                |     |
| .X±0.20           | .X'±1'     | 审核       | 张名         |       | 品名        | XA双排孔座         |  | 页次                  | 1/1 |
| .XX±0.15          | .XX'±0.5'  | CHECK    | 2013、07、03 |       | TITLE     |                |  | SHEET               |     |
| .XXX±0.10         | .XXX'±0.5' | 核准       | 张名         |       | 客户料号      |                |  |                     |     |
|                   |            | APPROVAL | 2013、07、03 |       | CUTM. NO. |                |  |                     |     |
|                   |            | 单位       | MM         | 比例    | 1:1       | 深圳市金航标电子有限公司   |  | www.kinghelm.com.cn |     |
|                   |            | UNITS    |            | SCALE |           | KH-A2508-2X04Y |  | 0755-28190160       |     |