

	1	2	3	4	5	6	7	8																																																																					
A																																																																													
B																																																																													
C																																																																													
D																																																																													
E	<p>技术参数</p> <p>间距: 1.25 温度范围: -25~+85°C 额定电压: 125V AC, DC 额定电流: 1.0A AC, DC 接触电阻: 20mΩ 绝缘电阻: 100MΩ 耐压: 500V AC/minute</p>					<table border="1"> <tr> <td rowspan="3">线性公差 / General Tolerance</td> <td>±0.2</td> <td></td> <td></td> <td></td> <td rowspan="3">材料 / Material</td> <td colspan="3" rowspan="3">           ①塑 座: LCP 本色            ②接 触 针: 磷铜 (镀锡)            ③焊 片: 磷铜 (镀锡)         </td> </tr> <tr> <td>±0.1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>±0.05</td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="3">角度公差 / Angle Tolerance</td> <td>±5.0°</td> <td></td> <td></td> <td></td> <td rowspan="3">品名 / ProduceName</td> <td colspan="3" rowspan="3">           ①塑 座: LCP 本色            ②接 触 针: 磷铜 (镀锡)            ③焊 片: 磷铜 (镀锡)         </td> </tr> <tr> <td>±3.0°</td> <td></td> <td></td> <td></td> </tr> <tr> <td>±1.0°</td> <td></td> <td></td> <td></td> </tr> <tr> <td>标记</td> <td colspan="2">变更内容</td> <td>签名</td> <td>年月日</td> <td rowspan="3">型号 / Model</td> <td colspan="3" rowspan="3"> <b>GH1.25 立贴 3P</b> </td> </tr> <tr> <td>绘图</td> <td>Lin L</td> <td>230509</td> <td></td> <td></td> </tr> <tr> <td>工艺</td> <td></td> <td></td> <td>批准</td> <td>Lin R 230509</td> </tr> <tr> <td>视角 / Projection</td> <td>审核</td> <td>Lin R 230509</td> <td></td> <td></td> <td>mm</td> <td>2.0</td> <td>1:1</td> <td></td> </tr> <tr> <td></td> <td>工艺</td> <td></td> <td></td> <td>批准</td> <td>Lin R 230509</td> <td colspan="3">共 1 张 第 1 张</td> </tr> </table>	线性公差 / General Tolerance	±0.2				材料 / Material	①塑 座: LCP 本色 ②接 触 针: 磷铜 (镀锡) ③焊 片: 磷铜 (镀锡)			±0.1				±0.05				角度公差 / Angle Tolerance	±5.0°				品名 / ProduceName	①塑 座: LCP 本色 ②接 触 针: 磷铜 (镀锡) ③焊 片: 磷铜 (镀锡)			±3.0°				±1.0°				标记	变更内容		签名	年月日	型号 / Model	<b>GH1.25 立贴 3P</b>			绘图	Lin L	230509			工艺			批准	Lin R 230509	视角 / Projection	审核	Lin R 230509			mm	2.0	1:1			工艺			批准	Lin R 230509	共 1 张 第 1 张		
线性公差 / General Tolerance	±0.2				材料 / Material	①塑 座: LCP 本色 ②接 触 针: 磷铜 (镀锡) ③焊 片: 磷铜 (镀锡)																																																																							
	±0.1																																																																												
	±0.05																																																																												
角度公差 / Angle Tolerance	±5.0°				品名 / ProduceName	①塑 座: LCP 本色 ②接 触 针: 磷铜 (镀锡) ③焊 片: 磷铜 (镀锡)																																																																							
	±3.0°																																																																												
	±1.0°																																																																												
标记	变更内容		签名	年月日	型号 / Model	<b>GH1.25 立贴 3P</b>																																																																							
绘图	Lin L	230509																																																																											
工艺			批准	Lin R 230509																																																																									
视角 / Projection	审核	Lin R 230509			mm	2.0	1:1																																																																						
	工艺			批准	Lin R 230509	共 1 张 第 1 张																																																																							
F																																																																													
	1	2	3	4	5	6	7	8																																																																					