

Coding profile - HC-MOD-K-CP - 1408562

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Coding profile for HC-MOD-K... housing



Product Description

Coding profile
Block with 8 pcs.

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 619301
GTIN	4046356619301
Weight per Piece (excluding packing)	10.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General

Color	red
Material	PA
Flammability rating according to UL 94	V2
Assembly instructions	for sleeve housing HC-MOD-K-TMS-.../panel mounting base HC-MOD-K-AFS-...

Standards and Regulations

Coding profile - HC-MOD-K-CP - 1408562

Technical data

Standards and Regulations


Flammability rating according to UL 94	V2
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 4.0	23090101
eCl@ss 4.1	23090101
eCl@ss 5.0	23090101
eCl@ss 5.1	23090101
eCl@ss 6.0	23090101
eCl@ss 7.0	23090101
eCl@ss 8.0	27440203
eCl@ss 9.0	27440203

ETIM

ETIM 4.0	EC000437
ETIM 5.0	EC002311
ETIM 6.0	EC002311

UNSPSC

UNSPSC 6.01	31161807
UNSPSC 7.0901	31161807
UNSPSC 11	31161807
UNSPSC 12.01	31161807



Coding profile - HC-MOD-K-CP - 1408562

Classifications

UNSPSC

UNSPSC 13.2	27112301
-------------	----------

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.AI30.B.01102
-----	--	--------------------------