Shell style/model

Contact type

Contact diameter

Codes

Free cable mount socket connector, female contact

Code 1

0.7mm

Solder type

100

Push-pull connectors female cable mount series


CCS1S1/04 4 pole

- Premium range of circular connectors
- IP68 sealed using vacuum technology (when connected and using environmental cable clamp)
- Tough, high performance interconnection
- Ideal for harsh and extreme environments
- · Suitable for broadcasting, autosport, military, rail, security and industrial applications
- Key coded to prevent misconnection
- · Will not disconnect when the cable is under load or stress
- · Cable mounting
- Tested to IEC 60512-3-5a
- Cable clamp required for use with this series





SOCKETS

PART NO.	DESCRIPTION	POLES	SERIES
CCS1S1/04	Female cable mount	4	CCS series



AWG 21-22
AVVG 21-22
0.79mm
1200V(AC) 1700V(DC)
1200V(AC) 1800V(DC)
5.5A
≤200V
5000 mating cycles
Brass (natural chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
PPS
Brass (gold plated)
<=95% [at 60°C /140°F]
15g [10 Hz - 2000 Hz]
100g [6 ms]
>72 hr
50/175/21
75 dB (10 MHz)
40 dB (1 GHz)
IP68 (when connected and using environmental cable clamp)





KEY FEATURES

Key coded | Cable mounting socket | Cable clamps required

This product should be used with the following cable clamps:

PART NO.	WIRE RANGE
CCV1C/CC	2.6 - 3.1mm
CCV1C/CD	3.1-3.6mm
CCV1C/CE	3.6-4.1mm
CCV1C/CF	4.1-4.3mm



Non IP68 cable clamps also available

A	C	C	Ε	S	S	0	R	ΙE	S

Metal and rubber caps for sockets

PART NO.	DESCRIPTION	
ССТ11	Camcirc metal cap for sockets A1	

PART NO.	DESCRIPTION
CCT12	Camcirc rubber cap for sockets A1



ASSOCIATED PRODUCTS

CCA1P1/A04

- CCA Series A1 size plug

page 103

