


Fast Switching Diode

General description

250mW SOD-323 Fast Switching Diode

SOD-323 Package



FEATURES

- Fast Switching Device
- Power Dissipation of 250mW
- High Stability and High Reliability
- Low reverse leakage
- Epoxy UL: 94V-0

Marking: A

Maximum Ratings & Thermal Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified.)

Parameters	Symbol	Value	Unit
Reverse Voltage	V_R	90	V
Peak Reverse Voltage	V_{RM}	80	V
Power Dissipation	P_d	250	mW
Operating junction temperature	T_j	150	°C
Storage temperature range	T_s	-55-+150	°C
Average Rectified Current	I_o	100	mA
Non-repetitive Peak Forward Current	I_{FM}	225	mA

Valid provided that electrodes are kept at ambient temperature.





Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified).


Parameter	Symbols	Test Condition	Limits		Unit
			Min	Max	
Reverse Leakage Current	I_R	$V_R=80V$		0.1	uA
Forward Voltage	V_F	$I_F=100mA$		1.20	V
Reverse Recovery Time	T_{RR}	$I_F= 10mA, R_L=100\Omega, V_R=6V$		4	nS
Capacitance	C_T	$V_R=0.5V, f=1MHz$		3	pF

1SS355

Typical Characteristics



SOD-323 PACKAGE OUTLINE Plastic surface mounted package



Symbol	Min.(mm)	Max.(mm)
A		1.000
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
L	0.475REF	
L1	0.250	0.400
θ	0°	8°

Important Notice and Disclaimer

DOESHARE has used reasonable care in preparing the information included in this document, but DOESHARE does not warrant that such information is error free. DOESHARE assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

DOESHARE no warranty, representation or guarantee regarding the documents, circuits and products specification, DOESHARE reservation rights to make changes for any documents, products, circuits and specifications at any time without notice.

Purchasers are solely responsible for the choice, selection and use of the DOESHARE products and services described herein, and DOESHARE assumes no liability whatsoever relating to the choice, selection or use of the products and services described herein.

No license, express or implied, by implication or otherwise under any intellectual property rights of DOESHARE.

Resale of DOESHARE products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by DOESHARE for the DOESHARE product or service described herein and shall not create or extend in any manner whatsoever, any liability of DOESHARE.